

CONTENTS

SINGLE SOURCE MANUFACTURER	12
NFPA 2016 STANDARDS	12
ULC COMPLIANCY	12
VEHICLE INSPECTION PROGRAM CERTIFICATION	13
PUMP TEST	13
GENERATOR TEST	13
BREATHING AIR TEST	13
UNITS OF MEASURE.....	13
BID BOND NOT REQUESTED.....	13
PERFORMANCE BOND NOT REQUESTED	14
APPROVAL DRAWING	14
ELECTRICAL WIRING DIAGRAMS	15
CHASSIS	15
WHEELBASE	15
GVW RATING.....	15
FRAME.....	15
FRONT AXLE.....	15
FRONT SUSPENSION	15
SHOCK ABSORBERS.....	16
FRONT OIL SEALS.....	16
FRONT TIRES	16
REAR AXLE	16
TOP SPEED OF VEHICLE.....	16
REAR SUSPENSION.....	16
REAR OIL SEALS	16
REAR TIRES.....	16
TIRE BALANCE.....	17
TIRE PRESSURE MANAGEMENT	17
FRONT HUB COVERS	17

REAR HUB COVERS.....	17
CHROME LUG NUT COVERS	17
MUD FLAPS	17
WHEEL CHOCKS	17
WHEEL CHOCK BRACKETS.....	17
ANTI-LOCK BRAKE SYSTEM	17
BRAKES.....	18
BRAKE SYSTEM AIR COMPRESSOR.....	18
BRAKE SYSTEM	18
BRAKE SYSTEM AIR DRYER.....	18
BRAKE LINES.....	19
AIR INLET	19
ENGINE.....	19
HIGH IDLE	19
ENGINE BRAKE	20
CLUTCH FAN.....	20
ENGINE AIR INTAKE.....	20
EXHAUST SYSTEM.....	20
RADIATOR.....	21
COOLANT LINES	21
FUEL TANK	22
DIESEL EXHAUST FLUID TANK	22
TRANSMISSION	22
TRANSMISSION SHIFTER.....	23
TRANSMISSION COOLER.....	23
DRIVELINE	23
STEERING	23
STEERING WHEEL	23
LOGO AND CUSTOMER DESIGNATION ON HORN BUTTON.....	24
BUMPER	24
GRAVEL PAN	24

HOSE TRAY	24
CENTER HOSE TRAY COVER	24
TOW HOOKS.....	24
CAB	25
CAB ROOF DRIP RAIL	26
INTERIOR CAB INSULATION	26
FENDER LINERS	26
PANORAMIC WINDSHIELD	26
WINDSHIELD WIPERS.....	26
ENGINE TUNNEL.....	27
INTERIOR CREW CAB REAR WALL ADJUSTABLE SEATING (PATENT PENDING).....	27
CAB REAR WALL EXTERIOR COVERING.....	27
CAB LIFT	27
Cab Lift Interlock.....	28
GRILLE	28
DOOR JAMB SCUFFPLATES.....	28
TRIM BAND ON CAB FACE.....	28
SIDE OF CAB MOLDING	28
MIRRORS.....	28
DOORS	28
DOOR PANELS	29
MANUAL CAB DOOR WINDOWS.....	29
CAB STEPS.....	29
STEP LIGHTS	29
FENDER CROWNS.....	30
CREW CAB WINDOWS	30
CAB INTERIOR.....	30
CAB INTERIOR UPHOLSTERY	30
CAB INTERIOR PAINT	31
CAB FLOOR	31
CAB DEFROSTER	31

CAB/CREW CAB HEATER.....	31
AIR CONDITIONING	32
SUN VISORS	32
GRAB HANDLES.....	32
ENGINE COMPARTMENT LIGHTS.....	32
ACCESS TO ENGINE DIPSTICKS	33
SEATING CAPACITY	33
DRIVER SEAT.....	33
OFFICER SEAT	33
RADIO COMPARTMENT	33
REAR FACING DRIVER SIDE OUTBOARD SEAT	33
REAR FACING PASSENGER SIDE OUTBOARD SEAT	34
FORWARD FACING CENTER SEATS.....	34
SEAT UPHOLSTERY.....	34
AIR BOTTLE HOLDERS.....	34
SEAT BELTS	34
HELMET STORAGE PROVIDED BY FIRE DEPARTMENT.....	35
CAB DOME LIGHTS	35
PORTABLE HAND LIGHTS, PROVIDED BY FIRE DEPARTMENT	35
CAB INSTRUMENTATION	35
GAUGES	35
INDICATOR LAMPS	36
ALARMS	37
INDICATOR LAMP AND ALARM PROVE-OUT.....	37
CONTROL SWITCHES.....	37
CUSTOM SWITCH PANELS	39
DIAGNOSTIC PANEL	39
AIR RESTRICTION INDICATOR.....	39
"DO NOT MOVE APPARATUS" INDICATOR	40
WIPER CONTROL	40
SPARE CIRCUIT	40

VEHICLE DATA RECORDER.....	40
Seat Belt Monitoring System.....	41
RADIO ANTENNA MOUNT.....	41
VEHICLE CAMERA SYSTEM.....	41
ELECTRICAL POWER CONTROL SYSTEM.....	42
VOLTAGE MONITOR SYSTEM.....	42
POWER AND GROUND STUDS.....	42
EMI/RFI PROTECTION.....	42
ELECTRICAL.....	43
BATTERY SYSTEM.....	44
BATTERY SYSTEM.....	44
MASTER BATTERY SWITCH.....	44
BATTERY COMPARTMENTS.....	44
JUMPER STUDS.....	45
BATTERY CHARGING RECEPTACLE.....	45
ALTERNATOR.....	45
ELECTRONIC LOAD MANAGEMENT.....	45
HEADLIGHTS.....	45
DIRECTIONAL LIGHTS.....	45
INTERMEDIATE LIGHT.....	46
CAB CLEARANCE/MARKER/ID LIGHTS.....	46
FRONT CAB SIDE DIRECTIONAL/MARKER LIGHTS.....	46
REAR CLEARANCE/MARKER/ID LIGHTING.....	46
REAR FMVSS LIGHTING.....	47
LICENSE PLATE BRACKET.....	47
LIGHTING BEZEL.....	47
BACK-UP ALARM.....	47
CAB PERIMETER SCENE LIGHTS.....	48
PUMP HOUSE PERIMETER LIGHTS.....	48
BODY PERIMETER SCENE LIGHTS.....	48
STEP LIGHTS.....	48

REAR WORK LIGHTS	48
HOSE BED LIGHTS	48
WALKING SURFACE LIGHT	49
WATER TANK	49
HOSE BED	50
HOSE BED DIVIDER.....	50
HOSE BED HOSE RESTRAINT.....	51
RUNNING BOARDS	51
TAILBOARD	51
REAR WALL, SMOOTH ALUMINUM/BODY MATERIAL.....	51
TOW BAR	52
COMPARTMENTATION	52
UNDERBODY SUPPORT SYSTEM	52
AGGRESSIVE WALKING SURFACE	53
LOUVERS	53
TESTING OF BODY DESIGN.....	53
LEFT SIDE COMPARTMENTATION	54
RIGHT SIDE COMPARTMENTATION	54
ROLLUP DOOR, SIDE COMPARTMENTS.....	55
COMPARTMENTATION, REAR.....	56
ROLLUP DOOR, REAR COMPARTMENT	56
COMPARTMENT LIGHTING.....	57
HATCH COMPARTMENT	57
HATCH COMPARTMENT	58
MOUNTING TRACKS	58
ADJUSTABLE SHELVES.....	58
SLIDE-OUT/TILT-DOWN TRAY	59
SLIDE-OUT FLOOR MOUNTED TRAY.....	59
RUB RAIL.....	60
BODY FENDER CROWNS.....	60
HARD SUCTION HOSE	60

HANDRAILS	60
AIR BOTTLE STORAGE (Double)	61
AIR BOTTLE COMPARTMENT STRAP	61
AIR BOTTLE STORAGE (Triple)	61
AIR BOTTLE COMPARTMENT STRAP	61
EXTENSION LADDER.....	61
ROOF LADDER.....	61
LADDER STORAGE.....	62
FOLDING LADDER.....	62
PIKE POLE PROVIDED BY FIRE DEPARTMENT	62
6' PIKE POLE PROVIDED BY FIRE DEPARTMENT.....	62
PIKE POLE STORAGE	63
STEPS	63
SWIMMING POOL STYLE LADDER.....	63
PUMP.....	63
PUMP PACKING.....	64
PUMP TRANSMISSION	64
PUMPING MODE.....	64
AIR PUMP SHIFT.....	65
TRANSMISSION LOCK-UP.....	65
AUXILIARY COOLING SYSTEM.....	65
INTAKE RELIEF VALVE.....	65
PRESSURE CONTROLLER	65
PRIMING PUMP	66
PUMP MANUALS.....	66
PLUMBING, STAINLESS STEEL AND HOSE	66
MAIN PUMP INLETS	66
MAIN PUMP INLET CAP.....	66
VALVES.....	67
LEFT SIDE INLET.....	67
INLET CONTROL.....	67

FRONT INLET PROVISION.....	67
INLET BLEEDER VALVE	67
TANK TO PUMP	67
TANK REFILL.....	67
LEFT SIDE DISCHARGE OUTLETS	68
RIGHT SIDE DISCHARGE OUTLETS.....	68
FRONT DISCHARGE OUTLET.....	68
REAR DISCHARGE OUTLET	68
DISCHARGE CAPS.....	68
OUTLET BLEEDER VALVE	68
LEFT SIDE OUTLET EBLAWS	69
RIGHT SIDE OUTLET ELBOWS	69
ADDITIONAL RIGHT SIDE OUTLET ELBOWS	69
REAR OUTLET ELBOWS.....	69
DISCHARGE OUTLET CONTROLS	69
DELUGE RISER	69
CROSSLAY HOSE BEDS	70
CROSSLAY/DEADLAY HOSE RESTRAINT.....	70
CROSSLAY 8.00" LOWER THAN STANDARD	70
FOAM CONCENTRATE PROPORTIONING SYSTEM PLUMBING (FUTURE INSTALL)	70
SINGLE FOAM TANK REFILL	70
FOAM TANK.....	71
FOAM TANK DRAIN	71
PUMP COMPARTMENT	71
PUMP MOUNTING.....	71
LEFT SIDE PUMP CONTROL PANELS	71
IDENTIFICATION TAGS	72
PUMP PANEL CONFIGURATION.....	72
PUMP AND GAUGE PANEL.....	72
PUMP COMPARTMENT LIGHT	73
VACUUM AND PRESSURE GAUGES	73

PRESSURE GAUGES.....	73
WATER LEVEL GAUGE.....	74
FOAM LEVEL GAUGE	74
LIGHT SHIELD	75
AIR HORN SYSTEM.....	75
Air Horn Location.....	75
AIR HORN CONTROL	75
ELECTRONIC SIREN	75
SPEAKER.....	76
FRONT ZONE UPPER WARNING LIGHTS.....	76
FRONT ZONE LOWER LIGHTS	77
HEADLIGHT FLASHER.....	77
SIDE ZONE LOWER LIGHTING.....	77
REAR ZONE LOWER LIGHTING.....	77
REAR/SIDE ZONE UPPER WARNING LIGHTS	77
LOOSE EQUIPMENT.....	78
NFPA REQUIRED LOOSE EQUIPMENT PROVIDED BY FIRE DEPARTMENT	78
SOFT SUCTION HOSE PROVIDED BY DEALER	79
DRY CHEMICAL EXTINGUISHER PROVIDED BY FIRE DEPARTMENT.....	79
WATER EXTINGUISHER PROVIDED BY FIRE DEPARTMENT.....	79
FLATHEAD AXE PROVIDED BY FIRE DEPARTMENT	79
PICKHEAD AXE PROVIDED BY FIRE DEPARTMENT.....	80
PAINT PROCESS	80
PAINT - ENVIRONMENTAL IMPACT.....	81
PAINT.....	82
PAINT CHASSIS FRAME ASSEMBLY	82
COMPARTMENT INTERIOR PAINT	83
REFLECTIVE STRIPES	83
REFLECTIVE STRIPE ON CAB FACE.....	83
REAR CHEVRON STRIPING.....	83
CAB DOOR REFLECTIVE STRIPE.....	83

FIRE APPARATUS PARTS CD MANUAL.....	83
SERVICE PARTS INTERNET SITE	84
CHASSIS SERVICE CD MANUALS	84
CHASSIS OPERATION CD MANUALS	84
ONE (1) YEAR MATERIAL AND WORKMANSHIP	84
ENGINE WARRANTY.....	85
STEERING GEAR WARRANTY	85
FIFTY (50) YEAR STRUCTURAL INTEGRITY	85
FRONT AXLE WARRANTY.....	85
REAR AXLE WARRANTY	85
BRAKE SYSTEM THREE (3) YEAR MATERIAL AND WORKMANSHIP WARRANTY	85
TEN (10) YEAR STRUCTURAL INTEGRITY.....	85
TEN (10) YEAR PRO-RATED PAINT AND CORROSION	85
CAMERA SYSTEM WARRANTY.....	85
COMPARTMENT LIGHT WARRANTY.....	86
TRANSMISSION WARRANTY.....	86
TRANSMISSION COOLER WARRANTY	86
WATER TANK WARRANTY	86
TEN (10) YEAR STRUCTURAL INTEGRITY	86
ROLL UP DOOR MATERIAL AND WORKMANSHIP WARRANTY	86
PUMP WARRANTY.....	86
TEN (10) YEAR PUMP PLUMBING WARRANTY	87
TEN (10) YEAR PRO-RATED PAINT AND CORROSION	87
VEHICLE STABILITY CERTIFICATION.....	87
ENGINE INSTALLATION CERTIFICATION	87
POWER STEERING CERTIFICATION.....	87
CAB INTEGRITY CERTIFICATION.....	87
CAB DOOR DURABILITY CERTIFICATION	88
WINDSHIELD WIPER DURABILITY CERTIFICATION	88
SEAT BELT ANCHOR STRENGTH.....	88
SEAT MOUNTING STRENGTH.....	88

CAB DEFROSTER CERTIFICATION88
CAB HEATER CERTIFICATION88
CAB AIR CONDITIONING PERFORMANCE CERTIFICATION89
AMP DRAW REPORT89

	Bidder Complies	
	Yes	No
<p><u>SINGLE SOURCE MANUFACTURER</u></p> <p>Bids shall only be accepted from a single source apparatus manufacturer. The definition of single source is a manufacturer that designs and manufactures their products using an integrated approach, including the chassis, cab weldment, cab, pumphouse (including the sheet metal enclosure, valve controls, piping and operator’s panel) and body being designed, fabricated and assembled on the bidder's premises. The electrical system (hardwire or multiplex) shall be both designed and integrated by the same apparatus manufacturer. The warranties relative to these major components (excluding component warranties such as engine, transmission, axles, pump, etc.) must be from a single source manufacturer and not split between manufacturers (i.e. body, pumphouse, cab weldment and chassis). The bidder shall provide evidence that they comply with this requirement.</p> <p>The bidder shall state the location of the factory where the apparatus is to be built.</p> <p><u>NFPA 2016 STANDARDS</u></p> <p>This unit shall comply with the NFPA standards effective January 1, 2016, except for fire department directed exceptions. These exceptions shall be set forth in the Statement of Exceptions.</p> <p>Certification of slip resistance of all stepping, standing and walking surfaces shall be supplied with delivery of the apparatus.</p> <p>All horizontal surfaces designated as a standing or walking surface that are greater than 48.00" above the ground must be defined by a 1.00" wide line along its outside perimeter. Perimeter markings and designated access paths to destination points shall be identified on the customer approval print and are shown as approximate. Actual location(s) shall be determined based on materials used and actual conditions at final build. Access paths may pass through hose storage areas and opening or removal of covers or restraints may be required. Access paths may require the operation of devices and equipment such as the aerial device or ladder rack.</p> <p>A plate that is highly visible to the driver while seated shall be provided. This plate shall show the overall height, length, and gross vehicle weight rating.</p> <p>The manufacturer shall have programs in place for training, proficiency testing and performance for any staff involved with certifications.</p> <p>An official of the company shall designate, in writing, who is qualified to witness and certify test results.</p> <p><u>ULC COMPLIANCY</u></p> <p>Apparatus proposed by the bidder shall meet the applicable requirements of the CAN/ULC-S515 standard as stated in the current edition at the time of contract execution. Fire department's</p>		

	Bidder Complies	
	Yes	No
<p>specifications that differ from ULC specifications shall be indicated in the proposal as "non-ULC" compliant. The apparatus shall be in service at an elevation of [Fill in Blank].</p> <p><u>VEHICLE INSPECTION PROGRAM CERTIFICATION</u></p> <p>To assure the vehicle is built to current CAN/ULC-S515 standards, the apparatus, in its entirety, shall be third-party, independent, audit-certified through Underwriters Laboratory (UL) that it is built and complies to all applicable standards in the current edition of CAN/ULC-S515. The certification includes: all design, production, operational, and performance testing of not only the apparatus, but those components that are installed on the apparatus (no exception).</p> <p>A placard shall be affixed in the driver's side area stating the third party agency, the date, the standard and the certificate number of the whole vehicle audit.</p> <p><u>PUMP TEST</u></p> <p>The pump shall be tested, approved and certified by Underwriter's Laboratory. The test results and the pump manufacturer's certification of hydrostatic test; the engine manufacturer's certified brake horsepower curve; and the manufacturer's record of pump construction details shall be forwarded to the Fire Department.</p> <p><u>GENERATOR TEST</u></p> <p>If the unit has a generator, the generator shall be tested, approved, and certified by Underwriters Laboratories. The test results shall be provided to the Fire Department at the time of delivery.</p> <p><u>BREATHING AIR TEST</u></p> <p>If the unit has breathing air, the apparatus manufacturer shall draw an air sample from the air system and certify that the air quality meets the requirements of CSA Z180.1-13, <i>Compressed Breathing Air and Systems</i>.</p> <p><u>UNITS OF MEASURE</u></p> <p>This apparatus shall be built for a destination in Canada and required ULC certifications shall be in the proper metric format such as liters, liters per minute, kpa, etc.</p> <p>The following specification contains standard US units of measure for volume, pressure, length/width/height, weight, etc. and are not converted to metric equivalents. However, specific individual options such as pressure gauges and speedometers may be described in metric terminology.</p> <p><u>BID BOND NOT REQUESTED</u></p> <p>A bid bond shall not be included. If requested, the following shall apply:</p> <p>All bidders shall provide a bid bond as security for the bid in the form of a 5% bid bond to accompany their bid. This bid bond shall be issued by a Surety Company who is listed on the U.S. Treasury Departments list of acceptable sureties as published in Department Circular 570.</p>		

	Bidder Complies	
	Yes	No
<p>The bid bond shall be issued by an authorized representative of the Surety Company and shall be accompanied by a certified power of attorney dated on or before the date of bid. The bid bond shall include language, which assures that the bidder/principal shall give a bond or bonds as may be specified in the bidding or contract documents, with good and sufficient surety for the faithful performance of the contract, including the Basic One (1) Year Limited Warranty, and for the prompt payment of labor and material furnished in the prosecution of the contract.</p> <p>Notwithstanding any document or assertion to the contrary, any surety bond related to the sale of a vehicle shall apply only to the Basic One (1) Year Limited Warranty for such vehicle. Any surety bond related to the sale of a vehicle shall not apply to any other warranties that are included within this bid (OEM or otherwise) or to the warranties (if any) of any third party of any part, component, attachment or accessory that is incorporated into or attached to the vehicle. In the event of any contradiction or inconsistency between this provision and any other document or assertion, this provision shall prevail.</p> <p><u>PERFORMANCE BOND NOT REQUESTED</u></p> <p>A performance bond shall not be included. If requested at a later date, one shall be provided to you for an additional cost and the following shall apply:</p> <p>The successful bidder shall furnish a Performance and Payment bond (Bond) equal to 100 percent of the total contract amount within 30 days of the notice of award. Such Bond shall be in a form acceptable to the Owner and issued by a surety company included within the Department of Treasury's Listing of Approved Sureties (Department Circular 570) with a minimum A.M. Best Financial Strength Rating of A and Size Category of XV. In the event of a bond issued by a surety of a lesser Size Category, a minimum Financial Strength rating of A+ is required.</p> <p>Bidder and Bidder's surety agree that the Bond issued hereunder, whether expressly stated or not, also includes the surety's guarantee of the vehicle manufacturer's Bumper to Bumper warranty period included within this proposal. Owner agrees that the penal amount of this bond shall be simultaneously amended to 25 percent of the total contract amount upon satisfactory acceptance and delivery of the vehicle(s) included herein. Notwithstanding anything contained within this contract to the contrary, the surety's liability for any warranties of any type shall not exceed three (3) years from the date of such satisfactory acceptance and delivery, or the actual Bumper to Bumper warranty period, whichever is shorter.</p> <p><u>APPROVAL DRAWING</u></p> <p>A drawing of the proposed apparatus shall be provided for approval before construction begins. The sales representative shall also have a copy of the same drawing. The finalized and approved drawing shall become part of the contract documents. This drawing shall indicate the chassis make and model, location of the lights, siren, horns, compartments, major components, etc.</p>		

	Bidder Complies	
	Yes	No
<p>A "revised" approval drawing of the apparatus shall be prepared and submitted by the manufacturer to the purchaser showing any changes made to the approval drawing.</p> <p><u>ELECTRICAL WIRING DIAGRAMS</u></p> <p>Two (2) electrical wiring diagrams, prepared for the model of chassis and body, shall be provided.</p> <p><u>CHASSIS</u></p> <p>Chassis provided shall be a new, tilt-type custom fire apparatus. The chassis shall be manufactured in the apparatus body builder's facility eliminating any split responsibility. The chassis shall be designed and manufactured for heavy-duty service, with adequate strength and capacity for the intended load to be sustained and the type of service required.</p> <p><u>WHEELBASE</u></p> <p>The wheelbase of the vehicle shall be no greater than 194.00.</p> <p><u>GVW RATING</u></p> <p>The gross vehicle weight rating shall be a minimum of 45,000.</p> <p><u>FRAME</u></p> <p>The chassis frame shall be built with two (2) steel channels bolted to five (5) cross members or more, depending on other options of the apparatus. The side rails shall be heat-treated steel measuring 10.25" x 3.50" x .375".</p> <p>Each rail shall have a section modulus of 16.00 cubic inches, yield strength of 120,000 psi, and a resisting bending moment (rbm) of 1,921,069 inch-pounds.</p> <p><u>FRONT AXLE</u></p> <p>The front axle shall be a reverse "I" beam type with inclined kingpins and a rated capacity of 18,000 lb.</p> <p><u>FRONT SUSPENSION</u></p> <p>The front springs shall be a three (3)-leaf, taper leaf design, 54.00" long x 4.00" wide, with a ground rating of 18,000 lb.</p> <p>The two (2) top leaves shall wrap the forward spring hanger pin. The top leaf shall also wrap the rear spring hanger pin. Both the front and rear eyes shall be Berlin style wraps that shall place the eyes in the horizontal plane within the main leaf. This shall reduce bending stress from acceleration and braking.</p> <p>A steel encased rubber bushing shall be used in the spring eye. The steel encased rubber bushing shall be maintenance free and require no lubrication.</p>		

	Bidder Complies	
	Yes	No
<p><u>SHOCK ABSORBERS</u> To provide a smoother ride, heavy-duty telescoping shock absorbers shall be provided on the front axle.</p> <p><u>FRONT OIL SEALS</u> Oil seals with viewing window shall be provided on the front axle.</p> <p><u>FRONT TIRES</u> Front tires shall be 315/80R22.50 radials, 20 ply tread, rated for 18,180 lb maximum axle load and 68 mph maximum speed.</p> <p>The tires shall be mounted on 22.50" x 9.00" polished aluminum disc wheels with a ten (10) stud, 11.25" bolt circle.</p> <p><u>REAR AXLE</u> The rear axle shall have a capacity of 27,000 lb.</p> <p><u>TOP SPEED OF VEHICLE</u> A rear axle ratio shall be furnished to allow the vehicle to reach a top speed of 68 mph.</p> <p><u>REAR SUSPENSION</u> The rear suspension shall be semi-elliptical, 3.00" wide x 53.00" long, 12-leaf pack with a ground rating of 27,000 lb. The spring hangers shall be castings.</p> <p>The two (2) top leaves shall wrap the forward spring hanger pin, and the rear of the spring shall be a slipper style end that shall ride in a rear slipper hanger. To reduce bending stress due to acceleration and braking, the front eye shall be a berlin eye that shall place the front spring pin in the horizontal plane within the main leaf.</p> <p>A steel encased rubber bushing shall be used in the spring eye. The steel encased rubber bushing shall be maintenance free and require no lubrication.</p> <p><u>REAR OIL SEALS</u> Oil seals shall be provided on the rear axle(s).</p> <p><u>REAR TIRES</u> Rear tires shall be four (4) 12R22.50 radials, 16 ply all season, rated for 27,120 lb maximum axle load and 75 mph maximum speed.</p> <p>The tires shall be mounted on 22.50" x 8.25" polished aluminum disc wheels with a ten (10) stud 11.25" bolt circle.</p>		

	Bidder Complies	
	Yes	No
<p><u>TIRE BALANCE</u> All tires shall be balanced with balancing beads. The beads shall be inserted into the tire and eliminate the need for wheel weights.</p> <p><u>TIRE PRESSURE MANAGEMENT</u> There shall be a LED tire alert pressure management system provided, that shall monitor each tire's pressure. A sensor shall be provided on the valve stem of each tire for a total of six (6) tires.</p> <p>The sensor shall calibrate to the tire pressure when installed on the valve stem for pressures between 10 and 200 psi. The sensor shall activate an integral battery operated LED when the pressure of that tire drops 5 to 8 psi.</p> <p>Removing the cap from the sensor shall indicate the functionality of the sensor and battery. If the sensor and battery are in working condition, the LED shall immediately start to flash.</p> <p><u>FRONT HUB COVERS</u> Stainless steel hub covers shall be provided on the front axle. An oil level viewing window shall be provided.</p> <p><u>REAR HUB COVERS</u> A pair of stainless steel high hat hub covers shall be provided on rear axle hubs.</p> <p><u>CHROME LUG NUT COVERS</u> Chrome lug nut covers shall be supplied on front and rear wheels.</p> <p><u>MUD FLAPS</u> Mud flaps shall be installed behind the front and rear wheels of the apparatus.</p> <p><u>WHEEL CHOCKS</u> There shall be one (1) pair of folding aluminum alloy wheel blocks, with easy-grip handle provided.</p> <p><u>WHEEL CHOCK BRACKETS</u> There shall be one (1) pair of horizontal mounting wheel chock brackets provided for the folding wheel chocks. The brackets shall be made of aluminum and consist of a quick release spring loaded rod to hold the wheel chocks in place. The brackets shall be mounted below the left side rear compartment.</p> <p><u>ANTI-LOCK BRAKE SYSTEM</u> The vehicle shall be equipped with an anti-lock braking system. The ABS shall provide a 4-channel anti-lock braking control on both the front and rear wheels. A digitally controlled system that utilizes microprocessor technology shall control the anti-lock braking system. Each</p>		

	Bidder Complies	
	Yes	No
<p>wheel shall be monitored by the system. When any particular wheel begins to lockup, a signal to be sent to the control unit. This control unit shall then reduce the braking of that wheel for a fraction of a second and then reapply the brake. This anti-lock brake system shall eliminate the lockup of any wheel thus helping to prevent the apparatus from skidding out of control.</p> <p><u>BRAKES</u></p> <p>The service brake system shall be a full air type design.</p> <p>Front brakes shall be disc type with automatic pad wear adjustment and 17.00" rotors for improved stopping distance.</p> <p>The rear brakes shall be 16.50" x 8.63" cam operated with automatic slack adjusters.</p> <p><u>BRAKE SYSTEM AIR COMPRESSOR</u></p> <p>The air compressor shall have 18.7 cubic feet per minute output.</p> <p><u>BRAKE SYSTEM</u></p> <p>The brake system shall include:</p> <ul style="list-style-type: none"> • Brake treadle valve • Heated automatic moisture ejector on air dryer • Total air system minimum capacity of 4,272 cubic inches • Two (2) air pressure gauges with a red warning light and an audible alarm, that activates when air pressure falls below 60 psi • Spring set parking brake system • Parking brake operated by a push-pull style control valve • A parking "brake on" indicator light on instrument panel • Park brake relay/inversion and anti-compounding valve, in conjunction with a double check valve system, with an automatic spring brake application at 40 psi • A pressure protection valve to prevent all air operated accessories from drawing air from the air system when the system pressure drops below 80 psi (550 kPa) • 1/4 turn drain valves on each air tank <p>The air tank shall be primed and painted to meet a minimum 750 hour salt spray test.</p> <p>To reduce the effects of corrosion, the air tank shall be mounted with stainless steel brackets (no exception).</p> <p><u>BRAKE SYSTEM AIR DRYER</u></p> <p>The air dryer shall be properly sized for the brake system with internal wet tank, spin-on coalescing filter cartridge and 100 watt heater.</p>		

Bidder Complies	
Yes	No

BRAKE LINES

Color-coded nylon brake lines shall be provided. The lines shall be wrapped in a heat protective loom where necessary in the chassis.

AIR INLET

One (1) air inlet with 3D series male coupling shall be provided. It shall allow station air to be supplied to the apparatus brake system through a shoreline hose. The inlet shall be located in the driver side lower step well of cab. A check valve shall be provided to prevent reverse flow of air. The inlet shall discharge into the "wet" tank of the brake system. A mating female fitting shall also be provided with the loose equipment.

ENGINE

The chassis shall be powered by an electronically controlled engine as described below:

Power:	450 hp at 2100 rpm
Torque:	1250 lb-ft at 1400 rpm
Governed Speed:	2200 rpm
Emissions Level:	EPA 2016
Fuel:	Diesel
Cylinders:	Six (6)
Displacement:	543 cubic inches (8.9L)
Starter:	Heavy duty
Fuel Filters:	Spin-on style primary filter with water separator and water-in-fuel sensor. Secondary spin-on style filter. Fuel system shall automatically reprime at start-up.

The engine shall include On-board diagnostics (OBD), which provides self-diagnostic and reporting. The system shall give the owner or repair technician access to state of health information for various vehicle sub systems. The system shall monitor vehicle systems, engine and after treatment. The system shall illuminate a malfunction indicator light on the dash console if a problem is detected.

HIGH IDLE

A high idle switch shall be provided, inside the cab, on the instrument panel, that shall automatically maintain a preset engine rpm. A switch shall be installed, at the cab instrument panel, for activation/deactivation.

	Bidder Complies	
	Yes	No
<p>The high idle shall be operational only when the parking brake is on and the truck transmission is in neutral. A green indicator light shall be provided, adjacent to the switch. The light shall illuminate when the above conditions are met. The light shall be labeled "OK to Engage High Idle."</p> <p><u>ENGINE BRAKE</u></p> <p>An engine brake is to be installed with the controls located on the instrument panel within easy reach of the driver.</p> <p>The driver shall be able to turn the engine brake system on/off and have a high, medium and low setting.</p> <p>The engine brake shall activate when the system is on and the throttle is released.</p> <p>The high setting of the brake application shall activate and work simultaneously with the variable geometry turbo (VGT) provided on the engine.</p> <p>The engine brake shall be installed in such a manner that when the engine brake is slowing the vehicle the brake lights are activated.</p> <p>The ABS system shall automatically disengage the auxiliary braking device, when required.</p> <p><u>CLUTCH FAN</u></p> <p>A fan clutch shall be provided. The fan clutch shall be automatic when the pump transmission is in "Road" position, and constantly engaged when in "Pump" position.</p> <p><u>ENGINE AIR INTAKE</u></p> <p>The engine air intake shall be located above the engine cooling package. It shall draw fresh air from the front of the apparatus through the radiator grille.</p> <p>A stainless steel metal screen shall be installed at the inlet of the air intake system that shall meet NFPA 1901 requirements.</p> <p>The air cleaner and stainless steel screen shall be easily accessible by tilting the cab.</p> <p><u>EXHAUST SYSTEM</u></p> <p>The exhaust system shall be stainless steel from the turbo to the inlet of the selective catalytic reduction (SCR) device, and shall be 4.00" in diameter. The exhaust system shall include a diesel particulate filter (DPF) and an SCR device to meet current EPA standards. An insulation wrap shall be provided on all exhaust pipes between the turbo and DPF to minimize the transfer of heat to the cab. The exhaust shall terminate horizontally ahead of the right side rear wheels. A tailpipe diffuser shall be provided to reduce the temperature of the exhaust as it exits. Heat</p>		

	Bidder Complies	
	Yes	No
<p>deflector shields shall be provided to isolate chassis and body components from the heat of the tailpipe diffuser.</p> <p><u>RADIATOR</u></p> <p>The radiator and the complete cooling system shall meet or exceed NFPA and engine manufacturer cooling system standards.</p> <p>For maximum corrosion resistance and cooling performance, the entire radiator core shall be constructed using long life aluminum alloy. The radiator core shall consist of aluminum fins, having a serpentine design, brazed to aluminum tubes. No solder joints or leaded material of any kind shall be acceptable in the core assembly.</p> <p>The radiator core shall have a minimum front area of 1060 square inches.</p> <p>Supply and return tanks shall be made of heavy duty glass-reinforced nylon that shall be crimped onto the core assembly using header tabs and a compression gasket to complete the radiator core assembly. There shall be a full steel frame around the inserts to enhance cooling system durability and reliability.</p> <p>The radiator shall be compatible with commercial antifreeze solutions.</p> <p>The radiator assembly shall be isolated from the chassis frame rails with rubber isolators to prevent the development of leaks caused by twisting or straining when the apparatus operates over uneven terrain.</p> <p>The radiator shall include a de-aeration/expansion tank. For visual coolant level inspection, the radiator shall have a built-in sight glass. The radiator shall be equipped with a 15 psi pressure relief cap.</p> <p>A drain port shall be located at the lowest point of the cooling system and/or the bottom of the radiator to permit complete flushing of the coolant from the system.</p> <p>Shields or baffles shall be provided to prevent recirculation of hot air to the inlet side of the radiator.</p> <p><u>COOLANT LINES</u></p> <p>Rubber hose shall be used for all engine coolant lines to be installed by the chassis manufacturer.</p> <p>Hose clamps shall be stainless steel constant torque type to prevent coolant leakage. They shall react to temperature changes in the cooling system and expand or contract accordingly while maintaining a constant clamping pressure on the hose.</p>		

	Bidder Complies	
	Yes	No
<p><u>FUEL TANK</u></p> <p>A 65 gallon fuel tank shall be provided and mounted at the rear of the chassis. The tank shall be constructed of 12-gauge, hot rolled steel. It shall be equipped with swash partitions and a vent. To eliminate the effects of corrosion, the fuel tank shall be mounted with stainless steel straps (no exception).</p> <p>A 0.75" drain plug shall be provided in a low point of the tank for drainage.</p> <p>A fill inlet shall be located on the left hand side of the body and be covered with a hinged, spring loaded, stainless steel door that is marked "Ultra Low Sulfur - Diesel Fuel Only."</p> <p>A 0.50" diameter vent shall be provided running from top of tank to just below fuel fill inlet.</p> <p>The tank shall meet all FHWA 393.67 requirements including a fill capacity of 95 percent of tank volume.</p> <p>All fuel lines shall be provided as recommended by the engine manufacturer.</p> <p><u>DIESEL EXHAUST FLUID TANK</u></p> <p>A 4.5 gallon diesel exhaust fluid (DEF) tank shall be provided and mounted in the driver's side body forward of the rear axle.</p> <p>A 0.50" drain plug shall be provided in a low point of the tank for drainage.</p> <p>A fill inlet shall be located on the driver's side of the body and be covered with a hinged, spring loaded, polished stainless steel door that is marked "Diesel Exhaust Fluid Only".</p> <p>The tank shall meet the engine manufacturer's requirement for 10 percent expansion space in the event of tank freezing.</p> <p>The tank shall include an integrated heater unit that utilizes engine coolant to thaw the DEF in the event of freezing.</p> <p><u>TRANSMISSION</u></p> <p>An electronic torque converting automatic transmission shall be provided.</p> <p>The transmission shall be equipped with prognostics to monitor oil life, filter life, and transmission health. A wrench icon on the shift selector's digital display shall indicate when service is due.</p> <p>Two (2) PTO openings shall be located on both sides of converter housing (positions 4 o'clock and 8 o'clock) as viewed from the rear.</p>		

Bidder Complies	
Yes	No

A transmission temperature gauge with red light and audible alarm shall be installed on the cab dash.

TRANSMISSION SHIFTER

A five (5)-speed push button shift module shall be mounted to right of driver on console. Shift position indicator shall be indirectly lit for after dark operation.

The transmission ratio shall be:

1st	3.49 to 1.00
2nd	1.86 to 1.00
3rd	1.41 to 1.00
4th	1.00 to 1.00
5th	0.75 to 1.00
R	5.03 to 1.00

TRANSMISSION COOLER

A plate and fin transmission oil cooler shall be provided using engine coolant to control the transmission oil temperature.

DRIVELINE

Drivelines shall be a heavy-duty metal tube and be equipped with universal joints.

The shafts shall be dynamically balanced before installation.

A splined slip joint shall be provided in each driveshaft.

STEERING

Steering gear shall be provided with integral heavy-duty power steering. For reduced system temperatures, the power steering shall incorporate an air to oil cooler and hydraulic pump with integral pressure and flow control. All power steering lines shall have wire braded lines with crimped fittings.

A tilt and telescopic steering column shall be provided to improve fit for a broader range of driver configurations.

STEERING WHEEL

The steering wheel shall be 18.00" in diameter, have tilting and telescoping capabilities, and a 4-spoke design.

	Bidder Complies	
	Yes	No
<p><u>LOGO AND CUSTOMER DESIGNATION ON HORN BUTTON</u></p> <p>The steering wheel shall have an emblem containing the fire apparatus manufacturer's logo and customer name. The emblem shall have three (3) rows of text for the customer's department name. There shall be a maximum of eight (8) characters in the first row, 11 characters in the second row and 11 characters in the third row.</p> <p>The first row of text shall be: TBD</p> <p>The second row of text shall be: TBD</p> <p>The third row of text shall be: TBD</p> <p><u>BUMPER</u></p> <p>A one (1) piece, stainless steel bumper shall be attached to the front of the frame.</p> <p>A 9.00" channel shall be mounted directly behind the bumper for additional strength.</p> <p>The bumper shall be extended 22.00" from front face of cab.</p> <p><u>GRAVEL PAN</u></p> <p>A gravel pan, constructed of bright aluminum treadplate, shall be furnished between the bumper and cab face. The gravel pan shall be properly supported from the underside to prevent flexing and vibration of the aluminum treadplate.</p> <p><u>HOSE TRAY</u></p> <p>A hose tray, constructed of aluminum, shall be placed in the center of the bumper extension.</p> <p>The tray shall have a capacity of 125' of 1.75" double jacket cotton-polyester hose.</p> <p>Black rubber grating shall be provided at the bottom of the tray. Drain holes are also provided.</p> <p><u>CENTER HOSE TRAY COVER</u></p> <p>A bright aluminum treadplate cover shall be provided over the center hose tray.</p> <p>The cover shall be attached with a stainless steel hinge.</p> <p>One (1) D-ring latch shall secure the cover in the closed position and a pneumatic stay arm shall hold the cover in the open position.</p> <p><u>TOW HOOKS</u></p> <p>Two (2) chromed steel tow hooks shall be installed under the bumper and attached to the front frame members. The tow hooks shall be designed and positioned to allow up to a 6,000 lb straight horizontal pull in line with the centerline of the vehicle. The tow hooks shall not be used for lifting of the apparatus.</p>		

	Bidder Complies	
	Yes	No
<p><u>CAB</u></p> <p>The cab shall be designed specifically for the fire service and manufactured by the chassis builder.</p> <p>The cab shall be built by the apparatus manufacturer in a facility located on the manufacturer's premises (no exception).</p> <p>For reasons of structural integrity and enhanced occupant protection, the cab shall be a heavy duty design, constructed to the following minimal standards.</p> <p>The cab shall have 12 main vertical structural members located in the A-pillar (front cab corner posts), B-pillar (side center posts), C-pillar (rear corner posts), and rear wall areas. The A-pillar shall be constructed of solid A356-T5 aluminum castings. The B-pillar and C-pillar shall be constructed from 0.13" wall extrusions. The rear wall shall be constructed of two (2) 2.00" x 2.00" outer aluminum extrusions and two (2) 2.00" x 1.00" inner aluminum extrusions. All main vertical structural members shall run from the floor to 4.625" x 3.864" x 0.090" thick roof extrusions to provide a cage-like structure with the A-pillar and roof extrusions being welded into a 0.25" thick corner casting at each of the front corners of the roof assembly.</p> <p>The front of the cab shall be constructed of a 0.13" firewall plate, covered with a 0.090" front skin (for a total thickness of 0.22"), and reinforced with a full width x 0.50" thick cross-cab support located just below the windshield and fully welded to the engine tunnel. The cross-cab support shall run the full width of the cab and weld to each A-pillar, the 0.13" firewall plate, and the front skin.</p> <p>The cab floors shall be constructed of 0.125" thick aluminum plate and reinforced at the firewall with an additional 0.25" thick cross-floor support providing a total thickness of 0.375" of structural material at the front floor area. The front floor area shall also be supported with two (2) triangular 0.30" wall extrusions that also provides the mounting point for the cab lift. This tubing shall run from the floor wireway of the cab to the engine tunnel side plates, creating the structure to support the forces created when lifting the cab.</p> <p>The cab shall be 96.00" wide (outside door skin to outside door skin) to maintain maximum maneuverability (no exception).</p> <p>The forward cab section shall have an overall height (from the cab roof to the ground) of approximately 99.00". The crew cab section shall have a 10.00" raised roof, with an overall cab height of approximately 109.00". The overall height listed shall be calculated based on a truck configuration with the lowest suspension weight rating, the smallest diameter tires for the suspension, no water weight, no loose equipment weight, and no personnel weight. Larger tires, wheels, and suspension shall increase the overall height listed.</p>		

	Bidder Complies	
	Yes	No
<p>The floor to ceiling height inside the crew cab shall be 64.50" in the center and outboard positions.</p> <p>The crew cab floor shall measure 46.00" from the rear wall to the back side of the rear facing seat risers.</p> <p>The engine tunnel, at the rearward highest point (knee level), shall measure 61.50" to the rear wall.</p> <p>The crew cab shall be a totally enclosed design with the interior area completely open to improve visibility and verbal communication between the occupants.</p> <p>The cab shall be a full tilt cab style.</p> <p>A 3-point cab mount system with rubber isolators shall improve ride quality by isolating chassis vibrations from the cab.</p> <p><u>CAB ROOF DRIP RAIL</u></p> <p>For enhanced protection from inclement weather, a drip rail shall be furnished on the sides of the cab. The drip rail shall be painted to match the cab roof, and bonded to the sides of the cab. The drip rail shall extend the full length of the cab roof.</p> <p><u>INTERIOR CAB INSULATION</u></p> <p>The cab shall include 1.00" insulation in the ceiling, 1.50" insulation in the side walls, and 2.00" insulation in the rear wall to maximize acoustic absorption and thermal insulation.</p> <p><u>FENDER LINERS</u></p> <p>Full circular inner fender liners in the wheel wells shall be provided.</p> <p><u>PANORAMIC WINDSHIELD</u></p> <p>A 1-piece safety glass windshield shall be provided with over 2,775 square inches of clear viewing area. The windshield shall be full width and shall provide the occupants with a panoramic view. The windshield shall consist of three (3) layers: outer light, middle safety laminate, and inner light. The outer light layer shall provide superior chip resistance. The middle safety laminate layer shall prevent the windshield glass pieces from detaching in the event of breakage. The inner light shall provide yet another chip resistant layer. The cab windshield shall be bonded to the aluminum windshield frame using a urethane adhesive. A custom frit pattern shall be applied on the outside perimeter of the windshield for a finished automotive appearance.</p> <p><u>WINDSHIELD WIPERS</u></p> <p>Three (3) electric windshield wipers with washer shall be provided that meet FMVSS and SAE requirements.</p>		

	Bidder Complies	
	Yes	No
<p>The washer reservoir shall be able to be filled without raising the cab.</p> <p><u>ENGINE TUNNEL</u></p> <p>Engine hood side walls shall be constructed of 0.375" aluminum. The top shall be constructed of 0.125" aluminum and shall be tapered at the top to allow for more driver and passenger elbow room.</p> <p>The engine hood shall be insulated for protection from heat and sound. The noise insulation keeps the dBA level within the limits stated in the current NFPA 1901 standards.</p> <p>The engine tunnel shall be no higher than 17.00" off the crew cab floor (no exception).</p> <p><u>INTERIOR CREW CAB REAR WALL ADJUSTABLE SEATING (PATENT PENDING)</u></p> <p>The interior rear wall of the crew cab shall have mounting holes every 2.75" to allow for adjustability of the forward facing crew cab seating along the rear wall. Seats shall be adjustable with use of simple hand tools allowing departments flexibility of their seating arrangement should their department needs change.</p> <p><u>CAB REAR WALL EXTERIOR COVERING</u></p> <p>The exterior surface of the rear wall of the cab shall be overlaid with bright aluminum treadplate that covers the entire rear wall</p> <p><u>CAB LIFT</u></p> <p>A hydraulic cab lift system shall be provided consisting of an electric powered hydraulic pump, dual lift cylinders, and necessary hoses and valves.</p> <p>Lift controls shall be located on the right side pump panel or front area of the body in a convenient location.</p> <p>The cab shall be capable of tilting 43 degrees to accommodate engine maintenance and removal.</p> <p>The cab shall be locked down by a 2-point normally closed spring loaded hook type latch that fully engages after the cab has been lowered. The system shall be hydraulically actuated to release the normally closed locks when the cab lift control is in the raised position and cab lift system is under pressure. When the cab is completely lowered and system pressure has been relieved, the spring loaded latch mechanisms shall return to the normally closed and locked position.</p> <p>The hydraulic cylinders shall be equipped with a velocity fuse that protects the cab from accidentally descending when the control is located in the tilt position.</p> <p>For increased safety, a redundant mechanical stay arm shall be provided that must be manually put in place on the left side between the chassis and cab frame when the cab is in the raised</p>		

	Bidder Complies	
	Yes	No
<p>position. This device shall be manually stowed to its original position before the cab can be lowered.</p> <p><u>Cab Lift Interlock</u> The cab lift system shall be interlocked to the parking brake. The cab tilt mechanism shall be active only when the parking brake is set and the ignition switch is in the on position. If the parking brake is released, the cab tilt mechanism shall be disabled.</p> <p><u>GRILLE</u> A single piece polished stainless steel grille and framework shall be provided on the front center of the cab.</p> <p><u>DOOR JAMB SCUFFPLATES</u> All cab door jambs shall be furnished with a polished stainless steel scuffplate, mounted on the striker side of the jamb.</p> <p><u>TRIM BAND ON CAB FACE</u> A 10.00" band of 22 gauge patterned stainless steel trim shall be installed across the front of the cab, from door hinge to door hinge. The trim band shall be centered on the headlights and applied with two-sided tape. A 0.625" self-adhesive trim strip shall be applied around the perimeter of the trim band.</p> <p><u>SIDE OF CAB MOLDING</u> Chrome molding shall be provided on both sides of cab.</p> <p><u>MIRRORS</u> A dual vision, motorized, west coast style mirror, with chrome finish, shall be mounted on each side of the front cab door with spring loaded retractable arms. The flat glass and convex glass shall be heated and adjustable with remote control within reach of the driver.</p> <p><u>DOORS</u> To enhance entry and egress to the cab, the forward cab door openings shall be a minimum of 37.50" wide x 63.37" high. The crew cab doors shall be located on the sides of the cab and shall be constructed in the same manner as the forward cab doors. The crew cab door openings shall be a minimum of 34.30" wide x 73.25" high.</p> <p>The forward cab and crew cab doors shall be constructed of extruded aluminum with a nominal material thickness of 0.093". The exterior door skins shall be constructed from 0.090" aluminum.</p> <p>A customized, vertical, pull-down type door handle shall be provided on the exterior of each cab door. The exterior handle shall be designed specifically for the fire service to prevent accidental activation, and shall provide 4.00" wide x 2.00" deep hand clearance for ease of use with heavy</p>		

	Bidder Complies	
	Yes	No
<p>gloved hands. Each door shall also be provided with an interior flush, open style paddle handle that shall be readily operable from fore and aft positions, and be designed to prevent accidental activation. The interior handles shall provide 4.00" wide x 1.25" deep hand clearance for ease of use with heavy gloved hands.</p> <p>The cab doors shall be provided with both interior (rotary knob) and exterior (keyed) locks exceeding FMVSS standards. The locks shall be capable of activating when the doors are open or closed. The doors shall remain locked if locks are activated when the doors are opened, then closed.</p> <p>A full length, heavy duty, stainless steel, piano-type hinge with a 0.38" pin and 11 gauge leaf shall be provided on all cab doors. There shall be double automotive-type rubber seals around the perimeter of the door framing and door edges to ensure a weather-tight fit.</p> <p>A chrome grab handle shall be provided on the inside of each cab door for ease of entry.</p> <p>The bottom cab step at each cab door location shall be located below the cab doors and shall be exposed to the exterior of the cab.</p> <p><u>DOOR PANELS</u> The inner cab door panels shall be constructed out of brushed stainless steel.</p> <p><u>MANUAL CAB DOOR WINDOWS</u> All cab entry doors shall contain a conventional roll down window.</p> <p><u>CAB STEPS</u> The forward cab and crew cab access steps shall be a full size two (2) step design to provide largest possible stepping surfaces for safe ingress and egress. The bottom steps shall be designed with a grip pattern punched into bright aluminum treadplate material to provide support, slip resistance, and drainage. The bottom steps shall be a bolt-in design to minimize repair costs should they need to be replaced. The forward cab steps shall be a minimum 25.00" wide, and the crew cab steps shall be 21.65" wide with a 10.00" minimum depth. The inside cab steps shall not exceed 16.50" in height. A slip-resistant handrail shall be provided adjacent to each cab door opening to assist during cab ingress and egress.</p> <p>The vertical surfaces of the step well shall be aluminum treadplate.</p> <p><u>STEP LIGHTS</u> There shall be six (6) white LED step lights installed for cab and crew cab access steps.</p> <ul style="list-style-type: none"> • One (1) light for the driver's access steps. • Two (2) lights for the driver's side crew cab access steps. • Two (2) lights for the passenger's side crew cab access steps. 		

	Bidder Complies	
	Yes	No
<ul style="list-style-type: none"> • One (1) light for the passenger's side access step. <p>In order to ensure exceptional illumination, each light shall provide a minimum of 25 foot-candles (fc) covering an entire 15" x 15" square placed ten (10) inches below the light and a minimum of 1.5 fc covering an entire 30" x 30" square at the same ten (10) inch distance below the light.</p> <p>The lights shall be activated when the battery switch is on and the adjacent door is opened.</p> <p><u>FENDER CROWNS</u></p> <p>Stainless steel fender crowns shall be installed at the cab wheel openings.</p> <p><u>CREW CAB WINDOWS</u></p> <p>One (1) fixed window with tinted glass shall be provided on each side of the cab, to the rear of the front cab door. The windows shall be sized to enhance light penetration into the cab interior. The windows shall measure 18.70" wide x 23.75" high.</p> <p><u>CAB INTERIOR</u></p> <p>The cab interior shall be constructed of primarily metal (painted aluminum) to withstand the severe duty cycles of the fire service.</p> <p>The officer side dash shall be a flat faced design to provide easy maintenance and shall be constructed out of painted aluminum.</p> <p>The instrument cluster shall be surrounded with a high impact ABS plastic contoured to the same shape of the instrument cluster.</p> <p>The engine tunnel shall be padded and covered, on the top and sides, with gray woven with black Imperial 1200 vinyl coated polyester.</p> <p>The headliner shall be installed in both forward and rear cab sections. Headliner material shall be vinyl. A sound barrier shall be part of its composition. Material shall be installed on aluminum sheet and securely fastened to interior cab ceiling.</p> <p>Forward portion of cab headliner shall permit easy access for service of electrical wiring or other maintenance needs.</p> <p>All wiring shall be placed in metal raceways. Routing through holes in tubing shall not be accepted due to chaffing that installation shall cause.</p> <p><u>CAB INTERIOR UPHOLSTERY</u></p> <p>The cab interior upholstery shall be dark silver gray.</p>		

	Bidder Complies	
	Yes	No
<p><u>CAB INTERIOR PAINT</u> The cab interior metal surfaces shall be painted fire smoke gray, vinyl texture paint.</p> <p><u>CAB FLOOR</u> The cab and crew cab floor areas shall be covered with floor mat consisting of a black pyramid rubber facing and closed cell foam decoupler.</p> <p>The top surface of the material has a series of raised pyramid shapes evenly spaced, which offer a superior grip surface. Additionally, the material has a 0.25" thick closed cell foam (no water absorption) which offers a sound dampening material for reducing sound levels.</p> <p><u>CAB DEFROSTER</u> To provide maximum defrost and heating performance, a 43,500 BTU heater-defroster unit with 350 CFM of air flow shall be provided inside the cab. The defroster unit shall be strategically located under the center forward portion of the vacuum formed instrument panel. For easy access, a removable vacuum formed cover shall be installed over the defroster unit. The defroster shall include an integral aluminum frame air filter, high performance dual scroll blowers, and ducts designed to provide maximum defrosting capabilities for the 1-piece windshield. The defroster ventilation shall be built into the design of the cab dash instrument panel and shall be easily removable for maintenance. The defroster shall be capable of clearing 98 percent of the windshield and side glass when tested under conditions where the cab has been cold soaked at 0 degrees Fahrenheit for 10 hours, and a 2 ounce per square inch layer of frost/ice has been able to build up on the exterior windshield. The defroster system shall meet or exceed SAE J382 requirements.</p> <p><u>CAB/CREW CAB HEATER</u> Two (2) 44,180 BTU auxiliary heaters with 276 CFM (each unit) of air flow shall be provided inside the crew cab, one (1) in each outboard rear-facing seat riser. The heaters shall include high performance dual scroll blowers, one (1) for each unit. Outlets for the heaters shall be located below each rear facing seat riser and below the fronts of the driver and passenger seats, for efficient airflow. An extruded aluminum plenum shall be incorporated in the cab structure that shall transfer heat to the forward cab seating positions.</p> <p>The heater/defroster and crew cab heaters shall be controlled by a single integral electronic control panel. The heater control panel shall allow the driver to control heat flow to the front and rear simultaneously. The control panel shall include variable adjustment for temperature and fan control, and be conveniently located on the dash in clear view of the driver. The control panel shall include highly visible, progressive LED indicators for both fan speed and temperature.</p>		

	Bidder Complies	
	Yes	No
<p><u>AIR CONDITIONING</u></p> <p>A high performance, customized air conditioning system shall be furnished inside the cab and crew cab.</p> <p>The air conditioning system shall be capable of cooling the average cab temperature from 100 degrees Fahrenheit to 75 degrees Fahrenheit within 30 minutes at 50 percent relative humidity. The cooling performance test shall be run only after the cab has been heat soaked at 100 degrees Fahrenheit for a minimum of 4 hours.</p> <p>A radiator mounted condenser with a 59,644 BTU output that meets and exceed the performance specification shall be installed. Mounting the condenser below the cab or body would reduce the performance of the system and shall not be acceptable.</p> <p>One (1) evaporator unit shall be installed in the center roof with two (2) cores, one (1) for the cab and one (1) for the crew cab. The evaporator unit shall have an adequate BTU rating to meet the performance specifications.</p> <p>Adjustable air outlets shall be strategically located on the evaporator cover per the following:</p> <ul style="list-style-type: none"> • Four (4) shall be directed towards the driver's location • Four (4) shall be directed towards the officer's location • Seven (7) shall be directed towards the crew cab area <p>The air conditioner refrigerant shall be R-134A and shall be installed by a certified technician.</p> <p>The air conditioner shall be controlled by a single electronic control panel. For ease of operation, the control panel shall include variable adjustment for temperature and fan control and be conveniently located on the dash in clear view of the driver.</p> <p><u>SUN VISORS</u></p> <p>Two (2) smoked polycarbonate sun visors provided. The sun visors shall be located above the windshield with one (1) mounted on each side of the cab.</p> <p>There shall be no retention bracket provided to help secure each sun visor in the stowed position.</p> <p><u>GRAB HANDLES</u></p> <p>A black rubber covered grab handle shall be mounted on the door post of the driver and officer's side cab door to assist in entering the cab. The grab handles shall be securely mounted to the post area between the door and windshield.</p> <p><u>ENGINE COMPARTMENT LIGHTS</u></p> <p>There shall be one (1) 12 volt DC, 3.00" white LED light(s) with chrome flange kit(s) installed under the cab to be used as engine compartment illumination.</p>		

	Bidder Complies	
	Yes	No
<p>These light(s) shall be activated automatically when the cab is raised.</p> <p><u>ACCESS TO ENGINE DIPSTICKS</u></p> <p>For access to the engine oil and transmission fluid dipsticks, there shall be a door on the engine tunnel, inside the crew cab. The door shall be on the rear wall of the engine tunnel, on the vertical surface.</p> <p>The engine oil dipstick shall allow for checking only. The transmission dipstick shall allow for both checking and filling.</p> <p>The door shall have a rubber seal for thermal and acoustic insulation. One (1) flush latch shall be provided on the access door.</p> <p><u>SEATING CAPACITY</u></p> <p>The seating capacity in the cab shall be six (6).</p> <p><u>DRIVER SEAT</u></p> <p>A scissor action, air ride, mid-height with headrest style seat shall be provided in the cab for the driver.</p> <p><u>OFFICER SEAT</u></p> <p>An SCBA seat shall be provided in the cab for the officer.</p> <p>The SCBA cavity shall be adjustable front to rear in 0.50" increments to accommodate different size SCBA bottles. Moving the SCBA cavity shall be accomplished by unbolting, relocating and re-bolting in the desired location.</p> <p><u>RADIO COMPARTMENT</u></p> <p>A radio compartment shall be provided under the officer's seat.</p> <p>The inside compartment dimensions shall be 16.00" wide x 7.50" high x 15.00" deep, with the back of the compartment angled up to match the cab structure.</p> <p>A drop-down door with a chrome plated lift and turn latch shall be provided for access.</p> <p>The compartment shall be constructed of smooth aluminum and painted to match the cab interior.</p> <p><u>REAR FACING DRIVER SIDE OUTBOARD SEAT</u></p> <p>One (1) rear facing SCBA seat shall be provided in the driver side outboard position in crew cab. The SCBA cavity shall be adjustable front to rear in 0.50" increments to accommodate different size SCBA bottles.</p>		

	Bidder Complies	
	Yes	No
<p>Moving the SCBA cavity shall be accomplished by unbolting, relocating, and re-bolting in the desired location.</p> <p><u>REAR FACING PASSENGER SIDE OUTBOARD SEAT</u></p> <p>There shall be one (1) rear facing SCBA seat provided at the passenger side outboard position in the crew cab.</p> <p>The SCBA cavity shall be adjustable front to rear in 0.50" increments to accommodate different size SCBA bottles. Moving the SCBA cavity shall be accomplished by unbolting, relocating and re-bolting in the desired location.</p> <p>The seat shall be furnished with a 3-point, shoulder type seat belt.</p> <p><u>FORWARD FACING CENTER SEATS</u></p> <p>There shall be two (2) forward facing, SCBA seats provided at the center position in the crew cab. The SCBA cavity shall be adjustable front to rear in 0.50" increments to accommodate different size SCBA bottles.</p> <p>Moving the SCBA cavity shall be accomplished by unbolting, relocating and re-bolting in the desired location.</p> <p><u>SEAT UPHOLSTERY</u></p> <p>All seat upholstery shall be gray woven with black water resistant material.</p> <p><u>AIR BOTTLE HOLDERS</u></p> <p>All SCBA type seats in the cab shall have a SCBA holder bracket. This bracket shall be compliant with the current NFPA 1901s standard and shall include a back plate, two (2) seats, a footplate and the strap to hold the bottle in the bracket. The bracket seats shall be a "one size fits all" style seat and shall accommodate SCBA cylinders from the high pressure 30-minute to the high pressure 60-minute. Seats shall be adjustable up and down by unbolting, relocating, and re-bolting in the desired position.</p> <p><u>SEAT BELTS</u></p> <p>All seating positions shall have red seat belts. The seat belts shall be furnished with a single automatic retractor. To provide quick, easy use for occupants wearing bunker gear, the female buckle and seat belt webbing length shall meet or exceed the current edition of NFPA 1901 and CAN/ULC - S515 standards.</p> <p>The 3-point shoulder type belts shall also include a D-loop assembly to the shoulder belt system. This feature adds an extender arm to the D-loop location placing the D-loop in a closer, easier to reach location.</p>		

	Bidder Complies	
	Yes	No
<p>To ensure safe operation, the seat shall be equipped with seat belt sensors in the seat cushion and belt receptacle that shall activate an alarm indicating a seat is occupied but not buckled.</p> <p><u>HELMET STORAGE PROVIDED BY FIRE DEPARTMENT</u> NFPA 1901, 2016 edition, section 14.1.7.4.1 requires a location for helmet storage be provided.</p> <p>There is no helmet storage on the apparatus as manufactured. The fire department shall provide a location for storage of helmets.</p> <p><u>CAB DOME LIGHTS</u> There shall be four (4) dual LED dome lights with black bezels provided. Two (2) lights shall be mounted above the inside shoulder of the driver and officer and two (2) lights shall be installed and located, one (1) on each side of the crew cab.</p> <p>The color of the LED's shall be red and white.</p> <p>The white LED's shall be controlled by the door switches and the lens switch.</p> <p>The color LED's shall be controlled by the lens switch.</p> <p>In order to ensure exceptional illumination, each white LED dome light shall provide a minimum of 10.1 foot-candles (fc) covering an entire 20.00" x 20.00" square seating position when mounted 40.00" above the seat.</p> <p><u>PORTABLE HAND LIGHTS, PROVIDED BY FIRE DEPARTMENT</u> NFPA 1901, 2016 edition, section 5.9.4 requires two portable hand lights mounted in brackets fastened to the apparatus.</p> <p>The hand lights are not on the apparatus as manufactured. The fire department shall provide and mount these hand lights.</p> <p><u>CAB INSTRUMENTATION</u> The cab instrument panel shall be a molded ABS panel and include gauges, telltale indicator lamps, control switches, alarms, and a diagnostic panel. The function of the instrument panel controls and switches shall be identified by a label adjacent to each item. Actuation of the headlight switch shall illuminate the labels in low light conditions. Telltale indicator lamps shall not be illuminated unless necessary. The cab instruments and controls shall be conveniently located within the forward cab section, forward of the driver. The gauge assembly and switch panels are designed to be removable for ease of service and low cost of ownership.</p> <p><u>GAUGES</u> The gauge panel shall include the following ten (10) black faced gauges with black bezels to monitor vehicle performance:</p>		

Bidder Complies	
Yes	No

- Voltmeter gauge (volts):
 - Low volts (11.8 VDC)
 - Amber telltale light on indicator light display with steady tone alarm
 - High volts (15.5 VDC)
 - Amber telltale light on indicator light display with steady tone alarm
- Engine Tachometer (RPM)
- Speedometer MPH (Major Scale), KM/H (Minor Scale)
- Fuel level gauge (Empty - Full in fractions):
 - Low fuel (1/8 full)
 - Amber indicator light in gauge dial with steady tone alarm
- Engine Oil pressure Gauge (PSI):
 - Low oil pressure to activate engine warning lights and alarms
 - Red indicator light in gauge dial with steady tone alarm
- Front Air Pressure Gauges (PSI):
 - Low air pressure to activate warning lights and alarm
 - Red indicator light in gauge dial with steady tone alarm
- Rear Air Pressure Gauges (PSI):
 - Low air pressure to activate warning lights and alarm
 - Red indicator light in gauge dial with steady tone alarm
- Transmission Oil Temperature Gauge (Fahrenheit):
 - High transmission oil temperature activates warning lights and alarm
 - Amber indicator light in gauge dial with steady tone alarm
- Engine Coolant Temperature Gauge (Fahrenheit):
 - High engine temperature activates an engine warning light and alarms
 - Red indicator light in gauge dial with steady tone alarm
- Diesel Exhaust Fluid Level Gauge (Empty - Full in fractions):
 - Low fluid (1/8 full)
 - Amber indicator light in gauge dial

INDICATOR LAMPS

To promote safety, the following telltale indicator lamps shall be located on the instrument panel in clear view of the driver. The indicator lamps shall be "dead-front" design that is only visible when active. The colored indicator lights shall have descriptive text or symbols.

The following amber telltale lamps shall be present:

- Low coolant
- Trac cntl (traction control) (where applicable)
- Check engine
- Check trans (check transmission)

	Bidder Complies	
	Yes	No
<ul style="list-style-type: none"> • Air rest (air restriction) • DPF (engine diesel particulate filter regeneration) • HET (engine high exhaust temperature) (where applicable) • ABS (antilock brake system) • MIL (engine emissions system malfunction indicator lamp) (where applicable) • Regen inhibit (engine emissions regeneration inhibit) (where applicable) • Side roll fault (where applicable) • Front air bag fault (where applicable) • Aux brake overheat (auxiliary brake overheat) (where applicable) • The following red telltale lamps shall be present: • Ladder rack down • Parking brake • Stop engine • The following green telltale lamps shall be present: • Left turn • Right turn • Battery on • Ignition • Aux brake (auxiliary brake engaged) (where applicable) • The following blue telltale lamps shall be present: • High beam <p><u>ALARMS</u></p> <p>Audible steady tone warning alarm: A steady audible tone alarm shall be provided whenever a warning condition is active.</p> <p><u>INDICATOR LAMP AND ALARM PROVE-OUT</u></p> <p>A system shall be provided which automatically tests telltale indicator lights and alarms located on the cab instrument panel. Telltale indicators and alarms shall perform prove-out for 3 to 5 seconds when the ignition switch is moved to the on position with the battery switch on.</p> <p><u>CONTROL SWITCHES</u></p> <p>For ease of use, the following controls shall be provided immediately adjacent to the cab instrument panel within easy reach of the driver. All switches shall have backlit labels for low light applications.</p> <p>Headlight/Parking light switch: A three (3)-position maintained rocker switch shall be provided. The first switch position shall deactivate all parking and headlights. The second switch position shall activate the parking lights. The third switch shall activate the headlights.</p>		

	Bidder Complies	
	Yes	No
<p>Panel back lighting intensity control switch: A three (3)-position momentary rocker switch shall be provided. Pressing the top half of the switch, "Panel Up" increases the panel back lighting intensity and pressing the bottom half of the switch, "Panel Down" decreases the panel back lighting intensity. Pressing the half or bottom half of the switch several times shall allow back lighting intensity to be gradually varied from minimum to maximum intensity level for ease of use.</p> <p>Ignition switch: A three (3)-position maintained/momentary rocker switch shall be provided. The first switch position shall turn off and deactivate vehicle ignition. The second switch position shall activate vehicle ignition and shall perform prove-out on the telltale indicators and alarms for 3 to 5 seconds after the switch is turned on. A green indicator lamp is activated with vehicle ignition. The third momentary position shall temporarily silence all active cab alarms. An alarm "chirp" may continue as long as alarm condition exists. Switching ignition to off position shall terminate the alarm silence feature and reset function of cab alarm system.</p> <p>Engine start switch: A two (2)-position momentary rocker switch shall be provided. The first switch position is the default switch position. The second switch position shall activate the vehicle's engine. The switch actuator is designed to prevent accidental activation.</p> <p>Hazard switch shall be provided on the instrument panel or on the steering column.</p> <p>Heater and defroster controls.</p> <p>Turn signal arm: A self-canceling turn signal with high beam headlight controls.</p> <p>Windshield wiper control shall have high, low, and intermittent modes.</p> <p>Parking brake control: An air actuated push/pull park brake control.</p> <p>Chassis horn control: Activation of the chassis horn control shall be provided through the center of the steering wheel.</p> <p>High idle engagement switch: A maintained rocker switch with integral indicator lamp shall be provided. The switch shall activate and deactivate the high idle function. The "OK To Engage High Idle" indicator lamp must be active for the high idle function to engage. A green indicator lamp integral to the high idle engagement switch shall indicate when the high idle function is engaged.</p> <p>"OK To Engage High Idle" indicator lamp: A green indicator light shall be provided next to the high idle activation switch to indicate that the interlocks have been met to allow high idle engagement.</p>		

	Bidder Complies	
	Yes	No
<p>Emergency switching shall be controlled by multiple individual warning light switches for various groups or areas of emergency warning lights. An Emergency Master switch provided on the instrument panel that enables or disables all individual warning light switches is included.</p> <p>An additional "Emergency Master" button shall be provided on the lower left hand corner of the gauge panel to allow convenient control of the "Emergency Master" system from inside the driver's door when standing on the ground.</p> <p><u>CUSTOM SWITCH PANELS</u></p> <p>The design of cab instrumentation shall allow for emergency lighting and other switches to be placed within easy reach of the operator thus improving safety. There shall be positions for up to four (4) switch panels in the lower instrument console and up to six (6) switch panels in the overhead visor console. All switches have backlit labels for low light conditions.</p> <p><u>DIAGNOSTIC PANEL</u></p> <p>A diagnostic panel shall be provided and accessible while standing on the ground. The panel shall be located inside the driver's side door left of the steering column. The diagnostic panel shall allow diagnostic tools such as computers to connect to various vehicle systems for improved troubleshooting providing a lower cost of ownership. Diagnostic switches shall allow ABS systems to provide blink codes should a problem exist.</p> <p>The diagnostic panel shall include the following:</p> <ul style="list-style-type: none"> • ENGINE/TRANSMISSION/ABS J1939 Diagnostic Port • ABS Diagnostic Switch and Indicator - The switch and amber indicator shall allow access to diagnostic mode and display of standard ABS system fault blink codes that may be generated by the ABS system • DPF REGEN (Diesel Particulate Filter Regeneration Switch) (where applicable) shall be provided to request regeneration of the engine emission system. An amber indicator shall be provided on top of the switch that shall illuminate in a "CHECK ENGINE" condition • REGEN INHIBIT (Diesel Particulate Filter Regeneration Inhibit Switch) (where applicable) shall be provided that shall request that regeneration be temporarily prevented. A green indicator shall be provided on top of the Regen Inhibit switch that shall illuminate when the Regen Inhibit feature is active. Regen Inhibit shall be disabled upon cycling of the ignition switch to the off state. <p><u>AIR RESTRICTION INDICATOR</u></p> <p>A high air restriction warning indicator light (electronic) shall be provided.</p>		

Bidder Complies	
Yes	No

"DO NOT MOVE APPARATUS" INDICATOR

A flashing red indicator light, located in the driving compartment, shall be illuminated automatically per the current NFPA requirements. The light shall be labeled "Do Not Move Apparatus If Light Is On."

The same circuit that activates the Do Not Move Apparatus indicator shall activate a pulsing alarm when the parking brake is released.

WIPER CONTROL

Wiper control shall consist of a two (2)-speed windshield wiper control with intermittent feature and windshield washer controls.

SPARE CIRCUIT

There shall be two (2) pair of wires, including a positive and a negative, installed on the apparatus.

The above wires shall have the following features:

- The positive wire shall be connected directly to the battery power
- The negative wire shall be connected to ground
- Wires shall be protected to 15 amps at 12 volts DC
- Power and ground shall terminate officer side dash area
- Termination shall be with 15 amp, power point plug with rubber cover
- Wires shall be sized to 125 percent of the protection

The circuit(s) may be load managed when the parking brake is set.

VEHICLE DATA RECORDER

There shall be a vehicle data recorder (VDR) capable of reading and storing vehicle information provided.

The information stored on the VDR can be downloaded through a USB port mounted in a convenient location determined by cab model. A USB cable can be used to connect the VDR to a laptop to retrieve required information. The program to download the information from the VDR will be available to download on-line.

The vehicle data recorder shall be capable of recording the following data via hardwired and/or CAN inputs:

- Vehicle Speed - MPH
- Acceleration - MPH/sec
- Deceleration - MPH/sec

	Bidder Complies	
	Yes	No
<ul style="list-style-type: none"> • Engine Speed - RPM • Engine Throttle Position - % of Full Throttle • ABS Event - On/Off • Seat Occupied Status - Yes/No by Position • Seat Belt Buckled Status - Yes/No by Position • Master Optical Warning Device Switch - On/Off • Time - 24 Hour Time • Date - Year/Month/Day <p><u>Seat Belt Monitoring System</u></p> <p>A seat belt monitoring system (SBMS) shall be provided. The SBMS shall be capable of monitoring up to 10 seating positions indicating the status of each seat position per the following:</p> <ul style="list-style-type: none"> • Seat Occupied & Buckled = Green LED indicator illuminated • Seat Occupied & Unbuckled = Red LED indicator with audible alarm • No Occupant & Buckled = Red LED indicator with audible alarm • No Occupant & Unbuckled = No indicator and no alarm <p>The SBMS shall include an audible alarm that shall warn that an unbuckled occupant condition exists and the parking brake is released, or the transmission is not in park.</p> <p><u>RADIO ANTENNA MOUNT</u></p> <p>There shall be one (1) standard 1.125", 18 thread antenna-mounting base(s) installed on the right side on the cab roof with high efficiency, low loss, coaxial cable(s) routed to the instrument panel area. A weatherproof cap shall be installed on the mount.</p> <p><u>VEHICLE CAMERA SYSTEM</u></p> <p>There shall be a color vehicle camera system provided with the following:</p> <ul style="list-style-type: none"> • One (1) camera located at the rear of the apparatus, pointing rearward, displayed automatically with the vehicle in reverse. <p>The camera image shall be displayed on a 7.00" LCD display located in view of the driver in the custom dash, per instrument panel layout. The display shall include manual camera activation capability and audio from the active camera.</p> <p>The following components shall be included:</p> <ul style="list-style-type: none"> • One (1) display • One (1) camera • All necessary cables 		

Bidder Complies	
Yes	No

ELECTRICAL POWER CONTROL SYSTEM

A compartment shall be provided in or under the cab to house the vehicle's electrical power and signal circuit protection and control components. The power and signal protection and control compartment shall contain circuit protection devices and power control devices. Power and signal protection and control components shall be protected against corrosion, excessive heat, excessive vibration, physical damage and water spray.

Serviceable components shall be readily accessible.

Circuit protection devices, which conform to SAE standard, shall be utilized to protect each circuit. All circuit protection devices shall be sized to prevent wire and component damage when subjected to extreme current overload. General protection circuit breakers shall be Type-I automatic reset (continuously resetting) and conform to SAE J553 or J258. When required, automotive type fuses conforming to SAE J554, J1284, J1888 or J2077 shall be utilized to protect electronic equipment.

Power control relays and solenoids shall have a direct current (dc) rating of 125 percent of the maximum current for which the circuit is protected.

Visual status indicators shall be supplied to identify control safety interlocks and vehicle status. In addition to visual status indicators, audible alarms designed to provide early warning of problems before they become critical shall be used.

VOLTAGE MONITOR SYSTEM

A voltage monitor system shall be provided to indicate the status of each battery system connected to the vehicle's electrical load. The monitor system shall provide visual and audio warning when the system voltage is above or below optimum levels.

POWER AND GROUND STUDS

Spare circuits shall be provided in the primary distribution center for two-way radio equipment.

The spare circuits shall consist of the following:

- One (1) 12-volt DC, 30 amp battery direct spare
- One (1) 12-volt DC ground and un-fused switched battery stud located in or adjacent to the power distribution center

EMI/RFI PROTECTION

The electrical system proposed shall include means to control undesired electromagnetic and radio frequency emissions. State of the art electrical system design and components shall be used to ensure radiated and conducted EMI (electromagnetic interference) and RFI (radio frequency interference) emissions are suppressed at their source.

	Bidder Complies	
	Yes	No
<p>The apparatus proposed shall have the ability to operate in the electromagnetic environment typically found in fire ground operations. The contractor shall be able to demonstrate the EMI and RFI testing has been done on similar apparatus and certifies that the vehicle proposed meets SAE J551 requirements.</p> <p>EMI/RFI susceptibility shall be controlled by applying immune circuit designs, shielding, twisted pair wiring and filtering. The electrical system shall be designed for full compatibility with low level control signals and high powered two-way radio communication systems. Harness and cable routing shall be given careful attention to minimize the potential for conducting and radiated EMI-RFI susceptibility.</p> <p><u>ELECTRICAL</u></p> <p>All 12-volt electrical equipment installed by the apparatus manufacturer shall conform to modern automotive practices. All wiring shall be high temperature crosslink type. Wiring shall be run, in loom or conduit, where exposed and have grommets where wire passes through sheet metal. Automatic reset circuit breakers shall be provided which conform to SAE Standards. Wiring shall be color, function and number coded. Function and number codes shall be continuously imprinted on all wiring harness conductors at 2.00" intervals. Exterior exposed wire connectors shall be positive locking, and environmentally sealed to withstand elements such as temperature extremes, moisture and automotive fluids.</p> <p>Electrical wiring and equipment shall be installed utilizing the following guidelines:</p> <ol style="list-style-type: none"> 1. All holes made in the roof shall be caulked with silicon, rope caulk is not acceptable. Large fender washers, liberally caulked, shall be used when fastening equipment to the underside of the cab roof. 2. Any electrical component that is installed in an exposed area shall be mounted in a manner that shall not allow moisture to accumulate in it. Exposed area shall be defined as any location outside of the cab or body. 3. Electrical components designed to be removed for maintenance shall not be fastened with nuts and bolts. Metal screws shall be used in mounting these devices. Also a coil of wire shall be provided behind the appliance to allow them to be pulled away from mounting area for inspection and service work. 4. Corrosion preventative compound shall be applied to all terminal plugs located outside of the cab or body. All non-waterproof connections shall require this compound IN the plug to prevent corrosion and for easy separation (of the plug). 5. All lights that have their sockets in a weather exposed area shall have corrosion preventative compound added to the socket terminal area. 6. All electrical terminals in exposed areas shall have silicon (1890) applied completely over the metal portion of the terminal. 		

	Bidder Complies	
	Yes	No
<p>All lights and reflectors, required to comply with Federal Motor Vehicle Safety Standard #108, shall be furnished. Rear identification lights shall be recessed mounted for protection. Lights and wiring mounted in the rear bulkheads shall be protected from damage by installing a false bulkhead inside the rear compartments.</p> <p>An operational test shall be conducted to ensure that any equipment that is permanently attached to the electrical system is properly connected and in working order.</p> <p>The results of the tests shall be recorded and provided to the purchaser at time of delivery.</p> <p><u>BATTERY SYSTEM</u></p> <p>There shall be four (4) 12 volt batteries that include the following features shall be provided:</p> <ul style="list-style-type: none"> • 950 CCA, cold cranking amps • 190 amp reserve capacity • High cycle • Group 31 • Rating of 3800 CCA at 0 degrees Fahrenheit • 760 minutes of reserve capacity • Threaded stainless steel studs <p>Each battery case shall be a black polypropylene material with a vertically ribbed container for increased vibration resistance. The cover shall be manifold vented with a central venting location to allow a 45 degree tilt capacity.</p> <p>The inside of each battery shall consist of a "maintenance free" grid construction with poly wrapped separators and a flooded epoxy bottom anchoring for maximum vibration resistance.</p> <p><u>BATTERY SYSTEM</u></p> <p>There shall be a single starting system with an ignition switch and starter button provided and located on the cab instrument panel.</p> <p><u>MASTER BATTERY SWITCH</u></p> <p>There shall be a master battery switch provided within the cab within easy reach of the driver to activate the battery system.</p> <p>An indicator light shall be provided on the instrument panel to notify the driver of the status of the battery system.</p> <p><u>BATTERY COMPARTMENTS</u></p> <p>Batteries shall be placed on non-corrosive mats and be stored in well ventilated compartments located under the cab.</p>		

	Bidder Complies	
	Yes	No
<p>Heavy-duty battery cables shall be used to provide maximum power to the electrical system. Cables shall be color coded.</p> <p>Battery terminal connections shall be coated with anti-corrosion compound. Battery solenoid terminal connections shall be encapsulated with semi-permanent rubberized compound.</p> <p><u>JUMPER STUDS</u></p> <p>One (1) set of battery jumper studs with plastic color-coded covers shall be included on the battery compartments.</p> <p><u>BATTERY CHARGING RECEPTACLE</u></p> <p>The battery charging receptacle location shall be adjacent to its respective battery (system).</p> <p><u>ALTERNATOR</u></p> <p>An alternator shall be provided that has a rated output current of 320 amps, as measured by SAE method J56. The alternator shall feature an integral regulator and rectifier system that has been tested and qualified to an ambient temperature of 257 degrees Fahrenheit (125 degrees Celsius). The alternator shall be connected to the power and ground distribution system with heavy-duty cables sized to carry the full rated alternator output.</p> <p><u>ELECTRONIC LOAD MANAGEMENT</u></p> <p>An electronic load management (ELM) system shall be provided that monitors the vehicles 12-volt electrical system, and automatically reduces the electrical load in the event of a low voltage condition and by doing so, ensures the integrity of the electrical system.</p> <p>The ELM shall monitor the vehicle's voltage while at the scene (parking brake applied). It shall sequentially shut down individual electrical loads when the system voltage drops below a preset value. Two (2) separate electrical loads shall be controlled by the load manager. The ELM shall sequentially re-energize electrical loads as the system voltage recovers.</p> <p><u>HEADLIGHTS</u></p> <p>There shall be four (4) rectangular halogen lights mounted in the front quad style, chrome housing on each side of the cab grille:</p> <ul style="list-style-type: none"> • The outside light on each side shall contain a halogen low and high beam module. • The inside light on each side shall contain a halogen high beam module only. <p><u>DIRECTIONAL LIGHTS</u></p> <p>There shall be two (2) amber LED populated arrow directional lights provided on the front of the cab, above the headlights. Each light shall be housed in the same quad common bezel as the front warning light. The [Color, Lens, LED's].</p>		

Bidder Complies	
Yes	No

INTERMEDIATE LIGHT

There shall be two (2) amber LED turn signal marker lights furnished, one (1) each side, in the rear fender panel. The light shall double as a turn signal and marker light.

CAB CLEARANCE/MARKER/ID LIGHTS

There shall be five (5) amber LED lights provided to indicate the presence and overall width of the vehicle in the following locations:

- Three (3) amber LED identification lights shall be installed in the center of the cab above the windshield.
- Two (2) amber LED clearance lights shall be installed, one (1) on each outboard side of the cab above the windshield.

FRONT CAB SIDE DIRECTIONAL/MARKER LIGHTS

There shall be two (2) amber LED lights installed front of the cab door, one (1) on each side of the cab.

The lights shall activate as marker lights with the headlight switch and directional lights with the corresponding directional circuit.

REAR CLEARANCE/MARKER/ID LIGHTING

There shall be a three (3) LED light bar used as identification lights located at the rear of the apparatus per the following:

- As close as practical to the vertical centerline
- Centers spaced not less than 6.00" or more than 12.00" apart
- Red in color
- All at the same height

There shall be two (2) LED lights installed at the rear of the apparatus used as clearance lights located at the rear of the apparatus per the following:

- To indicate the overall width of the vehicle
- One (1) each side of the vertical centerline
- As near the top as practical
- Red in color
- To be visible from the rear
- All at the same height

There shall be two (2) LED lights installed on the side of the apparatus used as marker lights as close to the rear as practical per the following:

	Bidder Complies	
	Yes	No
<ul style="list-style-type: none"> • To indicate the overall length of the vehicle • One (1) each side of the vertical centerline • As near the top as practical • Red in color • To be visible from the side • All at the same height <p>There shall be two (2) red reflectors located on the rear of the truck facing to the rear. One (1) each side, as far to the outside as practical, at a minimum of 15.00", but no more than 60.00", above the ground.</p> <p>There shall be two (2) red reflectors located on the side of the truck facing to the side. One (1) each side, as far to the rear as practical, at a minimum of 15.00", but no more than 60.00", above the ground.</p> <p>Per FMVSS 108 and CMVSS 108 requirements.</p> <p><u>REAR FMVSS LIGHTING</u></p> <p>There shall be the following stop/tail and directional lighting provided at the rear of the truck:</p> <ul style="list-style-type: none"> • Two (2) red LED stop/tail lights with clear lenses • Two (2) amber LED directional lights <p>The lights shall be mounted in a polished combination housing.</p> <p>Two (2) LED backup lights shall be provided.</p> <p><u>LICENSE PLATE BRACKET</u></p> <p>There shall be one (1) license plate bracket mounted on the rear of the body.</p> <p>A white LED light shall illuminate the license plate. A polished stainless steel light shield shall be provided over the light that shall direct illumination downward, preventing white light to the rear.</p> <p><u>LIGHTING BEZEL</u></p> <p>Two (2) four (4) light chrome plated composite plastic housings shall be provided for the rear stop/tail, directional, scene lights and warning</p> <p><u>BACK-UP ALARM</u></p> <p>A solid-state electronic audible back-up alarm that actuates when the truck is shifted into reverse shall be provided. The device shall sound at 60 pulses per minute and automatically adjust its volume to maintain a minimum ten (10) dBA above surrounding environmental noise levels.</p>		

	Bidder Complies	
	Yes	No
<p><u>CAB PERIMETER SCENE LIGHTS</u></p> <p>There shall be four (4) white LED lights with grommets provided, one(1) for each cab and crew cab door.</p> <p>These lights shall be activated automatically when the battery switch is on and the exit doors are opened or by the same means as the body perimeter scene lights.</p> <p><u>PUMP HOUSE PERIMETER LIGHTS</u></p> <p>There shall be two (2) 15.00" white 12 volt DC LED weatherproof strip lights provided under the pump panel running boards, one (1) each side.</p> <p>The lights shall be controlled by the same means as the body perimeter lights.</p> <p><u>BODY PERIMETER SCENE LIGHTS</u></p> <p>There shall be two (2) white LED lights with grommets provided under at the rear step area of the body, one (1) each side shining to the rear.</p> <p>The perimeter scene lights shall be activated when the parking brake is applied.</p> <p><u>STEP LIGHTS</u></p> <p>Four (4) white LED step lights shall be provided. One (1) step light shall be provided on each side, on the front compartment face and two (2) step lights at the rear to illuminate the tailboard.</p> <p>In order to ensure exceptional illumination, each light shall provide a minimum of 25 foot-candles (fc) covering an entire 15.00" x 15.00" square placed 10.00" below the light and a minimum of 1.5 fc covering an entire 30.00" x 30.00" square at the same 10.00" distance below the light.</p> <p>These step lights shall be actuated with the pump panel light switch.</p> <p>All other steps on the apparatus shall be illuminated per the current edition of NFPA 1901.</p> <p><u>REAR WORK LIGHTS</u></p> <p>There shall be one (1) pair of white 12 volt DC LED scene lights installed at the rear of the body to the outside of the rear compartment. The lights shall be directed down ward by a 40 degree angle and mounted with a chrome flange.</p> <p>The lights shall be controlled by a control from a switch at the rear of the truck.</p> <p><u>HOSE BED LIGHTS</u></p> <p>There shall be white 12 volt DC LED light strips with stainless steel protective cover, provided to light the hose bed area. Hose Bed lights shall meet the photometric levels listed in NFPA 1901 for Hose Bed lighting requirements.</p>		

	Bidder Complies	
	Yes	No
<ul style="list-style-type: none"> • Light strip(s) shall be installed along the upper edge of the left side of the hose bed. • Light strip(s) shall be installed along the upper edge of the right side of the hose bed. <p>The lights shall be activated by a cup switch at the rear of the apparatus no more than 62.00" from the ground.</p> <p><u>WALKING SURFACE LIGHT</u></p> <p>There shall be 4" round black 12 volt DC LED floodlight with bolt mount provided to illuminate the entire designated walking surface on top of the body.</p> <p>The light shall be activated when the body step lights are on.</p> <p><u>WATER TANK</u></p> <p>Booster tank shall have a capacity of 750 gallons and be constructed of polypropylene plastic.</p> <p>Tank joints and seams shall be nitrogen welded inside and out.</p> <p>Tank shall be baffled in accordance with NFPA Bulletin 1901 requirements.</p> <p>Baffles shall have vent openings at both the top and bottom to permit movement of air and water between compartments.</p> <p>Longitudinal partitions shall be constructed of .38" polypropylene plastic and shall extend from the bottom of the tank through the top cover to allow for positive welding.</p> <p>Transverse partitions shall extend from 4.00" off the bottom of the tank to the underside of the top cover.</p> <p>All partitions shall interlock and shall be welded to the tank bottom and sides.</p> <p>Tank top shall be constructed of .50" polypropylene. It shall be recessed .38" and shall be welded to the tank sides and the longitudinal partitions.</p> <p>Tank top shall be sufficiently supported to keep it rigid during fast filling conditions.</p> <p>Construction shall include 2.00" polypropylene dowels spaced no more than 30.00" apart and welded to the transverse partitions. Two (2) of the dowels shall be drilled and tapped (.50" diameter, 13.00" deep) to accommodate lifting eyes.</p> <p>A sump that is 8.00" long x 8.00" wide x 6.00" deep shall be provided at the bottom of the water tank.</p> <p>Sump shall include a drain plug and the tank outlet.</p> <p>Tank shall be installed in a fabricated cradle assembly constructed of structural steel.</p>		

	Bidder Complies	
	Yes	No
<p>Sufficient crossmembers shall be provided to properly support bottom of tank. Crossmembers shall be constructed of steel bar channel or rectangular tubing.</p> <p>Tank shall "float" in cradle to avoid torsional stress caused by chassis frame flexing. Rubber cushions, .50" thick x 3.00" wide, shall be placed on all horizontal surfaces that the tank rests on.</p> <p>Stops or other provision shall be provided to prevent an empty tank from bouncing excessively while moving vehicle.</p> <p>Mounting system shall be approved by the tank manufacturer.</p> <p>Fill tower shall be constructed of .50" polypropylene and shall be a minimum of 8.00" wide x 14.00" long.</p> <p>Fill tower shall be furnished with a .25" thick polypropylene screen and a hinged cover.</p> <p>An overflow pipe, constructed of 4.00" schedule 40 polypropylene, shall be installed approximately halfway down the fill tower and extend through the water tank and exit to the rear of the rear axle.</p> <p>One (1) sleeve shall be provided in the water tank for a 3.00" pipe to the rear.</p> <p><u>HOSE BED</u></p> <p>The hose bed shall be fabricated of .125"-5052 aluminum with a nominal 38,000 psi tensile strength.</p> <p>Standard hose bed width shall be 68.00" inside.</p> <p>Upper and rear edges of side panels shall have a double break for rigidity, a split tube finish shall not be acceptable.</p> <p>The upper inside area of the beavertails shall be covered with brushed stainless steel to prevent damage to painted surface when hose is removed.</p> <p>Flooring of the hose bed shall be removable aluminum grating with the top surface corrugated to aid in hose aeration. The grating slats shall be a minimum of 0.50" x 4.50" with spacing between slats for hose ventilation.</p> <p>The hose bed shall accommodate 1000 feet of 5.00" hose and 1000 feet of 3.00" hose.</p> <p><u>HOSE BED DIVIDER</u></p> <p>Two (2) adjustable hosebed dividers shall be furnished for separating hose.</p> <p>Each divider shall be constructed of a .25" brushed aluminum sheet. Flat surfaces shall be sanded for uniform appearance, or constructed of brushed aluminum.</p>		

	Bidder Complies	
	Yes	No
<p>Divider shall be fully adjustable by sliding in tracks, located at the front and rear of the hose bed.</p> <p>Divider shall be held in place by tightening bolts, at each end.</p> <p>Acorn nuts shall be installed on all bolts in the hose bed which have exposed threads.</p> <p><u>HOSE BED HOSE RESTRAINT</u></p> <p>The hose in the hose bed shall be restrained by a black nylon hook and loop strap at the top of the hose bed. At the rear of the hose bed, 2.00" black nylon webbing with a 1.50" x 4.00" box pattern shall attach at the top rear outside corners with seat belt buckle fasteners. The webbing shall have straps connected with seat belt buckle fasteners located at the rear body sheet below the hose bed.</p> <p>A cross-divider shall be provided just behind the fill tower. The divider shall be bolted to the side sheet.</p> <p><u>RUNNING BOARDS</u></p> <p>Running boards shall be fabricated of .125" bright aluminum treadplate.</p> <p>Each running board shall be supported by a welded 2.00" square tubing and channel assembly, which shall be bolted to the pump compartment substructure.</p> <p>Running boards shall be 12.75" deep and spaced .50" away from the pump panel.</p> <p>A splash guard shall be provided above the running board treadplate.</p> <p><u>TAILBOARD</u></p> <p>The tailboard shall also be constructed of .125" bright aluminum treadplate and spaced .50" from the body, as well as supported by a structural steel assembly.</p> <p>The tailboard area shall be 24.00" deep in the center area and 8.00" deep to the rear of the side compartments. The tailboard shall be T-shaped. The outboard sides of the tailboard shall be angled at 45 degrees beginning at the point where the body meets the tailboard at the outboard edge angling rearward to the rear edge of the tailboard.</p> <p>The exterior side shall be flanged down and in for increased rigidity of tailboard structure.</p> <p><u>REAR WALL, SMOOTH ALUMINUM/BODY MATERIAL</u></p> <p>The rear facing surfaces of the center rear wall shall be smooth aluminum.</p> <p>The bulkheads, the surface to the rear of the side body compartments, shall be smooth and the same material as the body.</p> <p>Any inboard facing surfaces below the height of the hosebed shall be aluminum diamond plate.</p>		

	Bidder Complies	
	Yes	No
<p><u>TOW BAR</u></p> <p>A tow bar shall be installed under the tailboard at center of truck.</p> <p>Tow bar shall be fabricated of 1.00" CRS bar rolled into a 3.00" radius.</p> <p>Tow bar assembly shall be constructed of .38" structural angle. When force is applied to the bar, it shall be transmitted to the frame rail.</p> <p>Tow bar assembly shall be designed and positioned to allow up to a 30-degree upward angled pull of 17,000 lb, or a 20,000 lb straight horizontal pull in line with the centerline of the vehicle.</p> <p>Tow bar design shall have been fully tested and evaluated using strain gauge testing and finite element analysis techniques.</p> <p><u>COMPARTMENTATION</u></p> <p>Body and compartments shall be fabricated of .125", 5052-H32 aluminum.</p> <p>Side compartments shall be an integral assembly with the rear fenders.</p> <p>Circular fender liners shall be provided for prevention of rust pockets and ease of maintenance.</p> <p>Compartment flooring shall be of the sweep out design with the floor higher than the compartment door lip.</p> <p>The compartment door opening shall be framed by flanging the edges in 1.75" and bending out again .75" to form an angle.</p> <p>Drip protection shall be provided above the doors by means of bright aluminum extrusion, formed bright aluminum treadplate or polished stainless steel.</p> <p>The top of the compartment shall be covered with bright aluminum treadplate rolled over the edges on the front, rear and outward side. These covers shall have the corners welded.</p> <p>Side compartment covers shall be separate from the compartment tops.</p> <p>Front facing compartment walls shall be covered with bright aluminum treadplate.</p> <p>All screws and bolts which protrude into a compartment shall have acorn nuts on the ends to prevent injury.</p> <p><u>UNDERBODY SUPPORT SYSTEM</u></p> <p>Due to the severe loading requirements of this pumper a method of body and compartment support suitable for the intended load shall be provided.</p>		

	Bidder Complies	
	Yes	No
<p>The backbone of the support system shall be the chassis frame rails which is the strongest component of the chassis and is designed for sustaining maximum loads.</p> <p>The support system shall include .375" thick steel vertical angle supports bolted to the chassis frame rails with .625" diameter bolts.</p> <p>Attached to the bottom of the steel vertical angles shall be horizontal angles, with gussets welded to the vertical members, which extend to the outside edge of the body.</p> <p>A steel frame shall be mounted on the top of these supports to create a floating substructure which shall result in a 500 lb equipment support rating per lower compartment.</p> <p>The floating substructure shall be separated from the horizontal members with neoprene elastomer isolators. These isolators shall reduce the natural flex stress of the chassis from being transmitted to the body.</p> <p>Isolators shall have a broad load range, proven viability in vehicular applications, be of a failsafe design and allow for all necessary movement in three (3) transitional and rotational modes.</p> <p>The neoprene isolators shall be installed in a modified V three (3)-point mounting pattern to reduce the natural flex of the chassis being transmitted to the body.</p> <p>A design with body compartments hanging on the chassis in an unsupported fashion shall not be acceptable.</p> <p><u>AGGRESSIVE WALKING SURFACE</u></p> <p>All exterior surfaces designated as stepping, standing, and walking areas shall comply with the required average slip resistance of the current NFPA standards.</p> <p><u>LOUVERS</u></p> <p>Louvers shall be stamped into compartment walls to provide the proper airflow inside the body compartments and to prevent water from dripping into the compartment. Where these louvers are provided, they shall be formed into the metal and not added to the compartment as a separate plate.</p> <p><u>TESTING OF BODY DESIGN</u></p> <p>Body structural analysis has been fully tested. Proven engineering and test techniques such as finite element analysis, stress coating and strain gauging shall be performed with special attention given to fatigue, life and structural integrity of the cab, body and substructure.</p> <p>Body shall be tested while loaded to its greatest in-service weight.</p> <p>The criteria used during the testing procedure shall include:</p>		

	Bidder Complies	
	Yes	No
<ul style="list-style-type: none"> • Raising opposite corners of the vehicle tires 9.00" to simulate the twisting a truck may experience when driving over a curb. • Making a 90 degree turn, while driving at 20 mph to simulate aggressive driving conditions. • Driving the vehicle at 35 mph on a washboard road. • Driving the vehicle at 55 mph on a smooth road. • Accelerating the vehicle fully, until reaching the approximate speed of 45 mph on rough pavement. <p>Evidence of actual testing techniques shall be made available upon request.</p> <p><u>LEFT SIDE COMPARTMENTATION</u></p> <p>The left side compartmentation shall consist of three rollup door compartments.</p> <p>A full height, rollup door compartment ahead of the rear wheels shall be provided. The interior dimensions of this compartment shall be 44.00" wide x 65.13" high x 25.75" deep. The clear door opening shall be a minimum of 38.25" wide x 56.88" high.</p> <p>A rollup door compartment over the rear wheels shall be provided. The interior dimensions of this compartment shall be 66.50" wide x 31.38" high x 25.75" deep. The clear door opening shall be a minimum of 58.25" wide x 23.13" high.</p> <p>A full height, rollup door compartment behind the rear wheels shall be provided. The interior dimensions of this compartment shall be 47.75" wide x 66.13" high x 25.75" deep. The clear door opening shall be a minimum of 44.75" wide x 57.88" high.</p> <p>The interior height of the compartments shall be measured from the compartment floor to the ceiling. The depth of the compartments shall be measured from the back wall to the inside of the door frame.</p> <p>Closing of the door shall not require releasing, unlocking, or unlatching any mechanism and shall easily be accomplished with one hand.</p> <p><u>RIGHT SIDE COMPARTMENTATION</u></p> <p>The right side compartmentation shall consist of three rollup door compartments.</p> <p>A full height, rollup door compartment ahead of the rear wheels shall be provided. The interior dimensions of this compartment shall be 44.00" wide x 66.63" high x 25.88" deep in the lower 25.00" of the compartment and 12.00" deep in the remaining upper portion. The clear door opening shall be a minimum of 38.25" wide x 56.88" high.</p>		

	Bidder Complies	
	Yes	No
<p>A rollup door compartment over the rear wheels shall be provided. The interior dimensions of this compartment shall be 66.50" wide x 32.88" high x 12.00" deep. The clear door opening shall be a minimum of 58.25" wide x 23.13" high.</p> <p>A full height, rollup door compartment behind the rear wheels shall be provided. The interior dimensions of this compartment shall be 47.75" wide x 67.63" high x 25.88" deep in the lower 26.00" of height and 12.00" deep in the remaining upper section of the compartment. The clear door opening shall be a minimum of 44.75" wide x 57.88" high.</p> <p>The interior height of the compartments shall be measured from the compartment floor to the ceiling. The depth of the compartments shall be measured from the back wall to the inside of the door frame.</p> <p>Closing of the door shall not require releasing, unlocking, or unlatching any mechanism and shall easily be accomplished with one hand.</p> <p><u>ROLLUP DOOR, SIDE COMPARTMENTS</u></p> <p>There shall be six (6) compartment doors installed on the side compartments. The doors shall be double faced aluminum construction and painted one (1) color to match the lower portion of the body.</p> <p>Lath sections shall be an interlocking rib design and shall be individually replaceable without complete disassembly of door.</p> <p>Between each slat at the pivoting joint shall be a PVC inner seal to prevent metal to metal contact and prevent dirt or moisture from entering the compartments. Seals shall allow door to operate in extreme temperatures ranging from plus 180 to minus 40 degrees Fahrenheit. Side, top and bottom seals shall be provided to resist ingress of dirt and weather and be made of Santoprene.</p> <p>All hinges, barrel clips and end pieces shall be nylon 66. All nylon components shall withstand temperatures from plus 300 to minus 40 degrees Fahrenheit. Hardened plastic shall not be acceptable.</p> <p>A polished stainless steel lift bar to be provided for each roll-up door. Lift bar shall be located at the bottom of door and have latches on the outer extrusion of the doors frame. A ledge shall be supplied over lift bar for additional area to aid in closing the door.</p> <p>Doors shall be constructed from an aluminum box section. The exterior surface of each slat shall be flat. The interior surfaces shall be concave to provide strength and prevent loose equipment from jamming the door from inside.</p>		

	Bidder Complies	
	Yes	No
<p>To conserve space in the compartments, the spring roller assembly shall not exceed 3.00" in diameter. A garage style roll door shall not be acceptable.</p> <p>The header for the rollup door assembly shall not exceed 4.00".</p> <p>A heavy-duty magnetic switch shall be used for control of open compartment door warning lights.</p> <p><u>COMPARTMENTATION, REAR</u></p> <p>A rollup door compartment above the rear tailboard shall be provided.</p> <p>Interior dimensions of this compartment shall be approximately 40.00" wide x 47.38" high x 25.88" deep in the lower 38.75" of height and 15.75" deep in the remaining upper portion. Depth of the compartment shall be calculated with the compartment door closed.</p> <p>For a chassis with a rear mounted fuel tank, a louvered removable access panel shall be furnished on the back wall of the compartment.</p> <p>Rear compartment shall be open into the rear side compartments.</p> <p>Clear door opening of this compartment shall be approximately 33.25" wide x 38.75" high.</p> <p>Closing of the door shall not require releasing, unlocking, or unlatching any mechanism and shall easily be accomplished with one hand.</p> <p><u>ROLLUP DOOR, REAR COMPARTMENT</u></p> <p>There shall be a rear rollup door. The door shall be double faced aluminum construction, an anodized satin finish.</p> <p>Lath sections shall be an interlocking rib design and shall be individually replaceable without complete disassembly of door.</p> <p>Between each slat at the pivoting joint shall be a PVC inner seal to prevent metal to metal contact and prevent dirt or moisture from entering the compartments. Seals shall allow door to operate in extreme temperatures ranging from plus 180 to minus 40 degrees Fahrenheit. Side, top and bottom seals shall be provided to resist ingress of dirt and weather and be made of Santoprene.</p> <p>All hinges, barrel clips and end pieces shall be nylon 66. All nylon components shall withstand temperatures from plus 300 to minus 40 degrees Fahrenheit. Hardened plastic shall not be acceptable.</p>		

	Bidder Complies	
	Yes	No
<p>A polished stainless steel lift bar to be provided for each roll-up door. Lift bar shall be located at the bottom of door and have latches on the outer extrusion of the doors frame. A ledge shall be supplied over lift bar for additional area to aid in closing the door.</p> <p>Door shall be constructed from an aluminum box section. The exterior surface of each slat shall be flat. The interior surface shall be concave to provide strength and prevent loose equipment from jamming the door from inside.</p> <p>To conserve space in the compartments, the spring roller assembly shall not exceed 3.00" in diameter. A garage style roll door shall not be acceptable.</p> <p>The header for the rollup door assembly shall not exceed 4.00".</p> <p>A heavy-duty magnetic switch shall be used for control of open compartment door warning lights.</p> <p><u>COMPARTMENT LIGHTING</u></p> <p>There shall be seven (7) compartment(s) with a single LED compartment light strip. Each light strip shall be centered vertically along the door framing. There shall be one (1) light per compartment. The single light strip shall be in [Location, Compartment Lights] compartment(s).</p> <p>Any remaining compartment without a light strip shall have a 6.00" diameter Truck-Lite, Model: 79384 light. Each light shall have a number 1076 one filament, two wire bulb.</p> <p>Opening the compartment door shall automatically turn the compartment lighting on.</p> <p><u>HATCH COMPARTMENT</u></p> <p>One (1) hatch compartment 161.25" long x 13.75" wide x 22.00" maximum depth shall be provided above the passenger side compartments, with two (2) liftup top opening hatch doors.</p> <p>Compartment shall extend the full length of the side body compartmentation.</p> <p>Sides of the compartment shall be constructed of the same material as the body and painted job color. A chrome and black vinyl molding shall be provided to cover the seam between the top of the body panel and the bottom of the hatch compartment.</p> <p>Top of the compartment shall be constructed of bright aluminum treadplate.</p> <p>Two (2) liftup, bright aluminum treadplate doors shall be provided on the top of the compartment, each with a chrome grab handle.</p> <p>Doors shall have lipped edges with a rubber seal for weather resistance, and an inner pan with one (1) recessed light.</p>		

	Bidder Complies	
	Yes	No
<p>Doors shall be hinged on the outboard side and shall be held open with rubber covered chains.</p> <p>One (1) socket and plunger type latch shall be provided with each door to hold the doors in the closed position.</p> <p>Each door shall have a clear door opening of 64.00" long x 7.50" wide.</p> <p>Compartment shall drain to an area below the hose bed.</p> <p><u>HATCH COMPARTMENT</u></p> <p>One (1) hatch compartment 161.25" long x 27.75" wide x 22.00" maximum depth shall be provided above the driver side compartments, with two (2) lift up top opening hatch doors.</p> <p>Compartment shall extend the full length of the side body compartmentation.</p> <p>Sides of the compartment shall be constructed of the same material as the body and painted job color. A chrome and black vinyl molding shall be provided to cover the seam between the top of the body panel and the bottom of the hatch compartment.</p> <p>Top of the compartment shall be constructed of bright aluminum treadplate.</p> <p>Two (2) lift-up, bright aluminum treadplate doors shall be provided on the top of the compartment, each with a chrome grab handle.</p> <p>Doors shall have lipped edges with a rubber seal for weather resistance, and an inner pan with one (1) recessed light.</p> <p>Doors shall be hinged on the outboard side and shall be held open with pneumatic stay arms.</p> <p>One (1) socket and plunger type latch shall be provided with each door to hold the doors in the closed position.</p> <p>Each door shall have a clear door opening of 64.00" long x 21.50" wide.</p> <p>Compartment shall drain to an area below the hose bed.</p> <p><u>MOUNTING TRACKS</u></p> <p>There shall be seven (7) sets of tracks for mounting shelf(s) in D3, D2, D1, R1, P1, P2 and P3. These tracks shall be installed vertically to support the adjustable shelf(s), and shall be full height of the compartment. The tracks shall be unpainted with a natural finish.</p> <p><u>ADJUSTABLE SHELVES</u></p> <p>There shall be six (6) shelves with a capacity of 500 lb provided. The shelf construction shall consist of .188" aluminum with 2.00" sides. Each shelf shall be painted to match the</p>		

	Bidder Complies	
	Yes	No
<p>compartment interior. Each shelf shall be infinitely adjustable by means of a threaded fastener, which slides in a track.</p> <p>The shelves shall be held in place by .12" thick stamped plated brackets and bolts.</p> <p>The location shall be One (1) shelf in upper portion of D1, D3, R1, P1, P2, P3.</p> <p><u>SLIDE-OUT/TILT-DOWN TRAY</u></p> <p>There shall be one (1) slide-out tray provided.</p> <p>The bottom of each tray shall constructed of 0.188" thick aluminum while special aluminum extrusions shall be utilized for the tray sides, ends, and tracks. The corners shall be welded to form a rigid unit.</p> <p>A spring loaded lock shall be provided on each side at the front of the tray. Releasing the locks shall allow the tray to slide out approximately two-thirds (2/3) of its length from the stowed position and tip 30 degrees down from horizontal. The tray shall be equipped with ball bearing rollers for smooth operation.</p> <p>Rubber padded stops shall be provided for the tray in the extended positions.</p> <p>The capacity rating of the tray shall be a minimum of 215 lb in the extended position.</p> <p>The vertical position of the tray within the compartment shall be adjustable.</p> <p>The tray(s) shall be located in D1.</p> <p><u>SLIDE-OUT FLOOR MOUNTED TRAY</u></p> <p>There shall be two (2) floor mounted slide-out tray(s) provided.</p> <p>Each tray shall have 2.00" high sides and a minimum capacity rating of 500 lb in the extended position.</p> <p>Each tray shall be constructed of aluminum painted spatter gray</p> <p>There shall be two undermount-roller bearing type slides rated at 250lb each provided. The pair of slides shall have a safety factor rating of 2.</p> <p>To ensure years of dependable service, the slides shall be coated with a finish that is tested to withstand a minimum of 1,000 hours of salt spray per ASTM B117.</p> <p>To ensure years of easy operation, the slides shall require no more than a 50lb force for push-in or pull-out movement when fully loaded after having been subjected to a 40 hour vibration (shaker) test under full load. The vibration drive file shall have been generated from</p>		

	Bidder Complies	
	Yes	No
<p>accelerometer data collected from a heavy truck chassis driven over rough gravel roads in an unloaded condition. Proof of compliance shall be provided upon request.</p> <p>Automatic locks shall be provided for both the "in" and "out" positions. The trip mechanism for the locks shall be located at the front of the tray for ease of use with a gloved hand.</p> <p>The location(s) shall be D1 and D3.</p> <p><u>RUB RAIL</u></p> <p>Bottom edge of the side compartments shall be trimmed with a bright aluminum extruded rub rail.</p> <p>Trim shall be 2.12" high with 1.38" flanges turned outward for rigidity.</p> <p>The rub rails shall not be an integral part of the body construction, which allows replacement in the event of damage.</p> <p><u>BODY FENDER CROWNS</u></p> <p>Stainless steel fender crowns shall be provided around the rear wheel openings.</p> <p>A rubber welting shall be provided between the body and the crown to seal the seam and restrict moisture from entering.</p> <p>A dielectric barrier shall be provided between the fender crown fasteners (screws) and the fender sheet metal to prevent corrosion.</p> <p><u>HARD SUCTION HOSE</u></p> <p>Hard suction hose shall not be required.</p> <p><u>HANDRAILS</u></p> <p>The handrails shall be 1.25" diameter anodized aluminum extrusion, with a ribbed design, to provide a positive gripping surface.</p> <p>Chrome plated end stanchions shall support the handrail. Plastic gaskets shall be used between end stanchions and any painted surfaces.</p> <p>Drain holes shall be provided in the bottom of all vertically mounted handrails.</p> <p>Handrails shall be provided to meet NFPA 1901 section 15.8 requirements. The handrails shall be installed as noted on the sales drawing.</p> <p>One (1) vertical handrail, not less than 29.00" long, shall be located on the passenger side rear beavertail.</p>		

	Bidder Complies	
	Yes	No
<ul style="list-style-type: none"> One (1) full width horizontal handrail shall be provided below the hose bed at the rear of the apparatus. <p>- Two (2) handrails 12.00" handrails shall be provided mounted (1) Top of pumphouse DS, (1) DS body side sheet.</p> <p><u>AIR BOTTLE STORAGE (DOUBLE)</u> A quantity of two (2) air bottle compartments, 15.25" wide x 7.75" tall x 26.00" deep, shall be provided on the driver side forward of the rear wheels. The triangular door shall cover the double air bottle opening and the DEF tank access. and on the driver side rearward of the rear wheels. The triangular door shall cover the double air bottle opening and the fuel tank access. . A polished stainless steel door with a chrome plated flush lift & turn latch shall be provided to contain the air bottle. A dielectric barrier shall be provided between the door hinge, hinge fasteners and the body sheet metal.</p> <p>Inside the compartment, black rubber matting shall be provided.</p> <p><u>AIR BOTTLE COMPARTMENT STRAP</u> A strap shall be provided in the air bottle compartment to help contain the air bottle when the vehicle is parked on an incline. The strap shall wrap around the neck and attach to the wall of the compartment.</p> <p><u>AIR BOTTLE STORAGE (TRIPLE)</u> A quantity of two (2) air bottle compartments designed to hold (3) air bottles up to 7.25" in diameter x 26.00" deep shall be provided on the passenger side forward of the rear wheels and on the passenger side rearward of the rear wheels. A polished stainless steel door with a chrome plated flush lift & turn latch shall be provided to contain the air bottle. A dielectric barrier shall be provided between the door hinge, hinge fasteners and the body sheet metal.</p> <p>Inside the compartment, black rubber matting shall be provided.</p> <p><u>AIR BOTTLE COMPARTMENT STRAP</u> A strap shall be provided in the air bottle compartment(s) to help contain the air bottles when the vehicle is parked on an incline. The strap shall wrap around the neck and attach to the wall of the compartment.</p> <p><u>EXTENSION LADDER</u> There shall be a 24' two-section aluminum extension ladder provided.</p> <p><u>ROOF LADDER</u> There shall be a 14' aluminum roof ladder provided.</p>		

	Bidder Complies	
	Yes	No
<p><u>LADDER STORAGE</u></p> <p>The ladders shall be stored between the water tank and the passenger's side compartments.</p> <p>The ladders shall extend into the pump compartment just to the rear of the water pump discharges.</p> <p>The ladder storage area shall be enclosed as practical by means of sheet metal to protect the ladders from road dirt. The ladders that extend into the pump house shall also be enclosed. A black rubber boot shall be provided to enclose the ladders in the gap between the pump house and the body.</p> <p>Each ladder shall be stored vertically in a separate stainless steel storage trough. Each stainless steel trough shall be lined with nylon slides.</p> <p>An aluminum enclosure shall be provided at the rear of the body to properly contain the ladders. This enclosure shall extend to the rear of the side body compartments.</p> <p>The enclosure shall also include a vertically hinged smooth aluminum door with a D-handle latch to access the ladders.</p> <p><u>FOLDING LADDER</u></p> <p>One (1) 10.00' aluminum folding ladder shall be installed in a U-shaped trough inside the ladder storage compartment.</p> <p><u>PIKE POLE PROVIDED BY FIRE DEPARTMENT</u></p> <p>NFPA 1901, 2016 edition, Section 5.9.4 requires one (1) 8 ft or longer pike pole mounted in a bracket fastened to the apparatus.</p> <p>The pike pole is not on the apparatus as manufactured. The fire department shall provide and mount the pike pole.</p> <p>The pike pole(s) shall be a Akron 10' pike pole.</p> <p><u>6' PIKE POLE PROVIDED BY FIRE DEPARTMENT</u></p> <p>NFPA 1901, 2016 edition, Section 5.9.4 requires one (1) 6' pike pole or plaster hook mounted in a bracket fastened to the apparatus.</p> <p>The pike pole is not on the apparatus as manufactured. The fire department shall provide and mount the pike pole.</p> <p>The pike pole(s) shall be an Akron 6' pike pole.</p>		

	Bidder Complies	
	Yes	No
<p><u>PIKE POLE STORAGE</u></p> <p>Aluminum tubing shall be used for the storage of two (2) pike poles and shall be located in ladder storage compartment. If the head of a pike pole can come in contact with a painted surface, a stainless steel scuffplate shall be provided.</p> <p><u>STEPS</u></p> <p>A folding step shall be provided on the front of each fender compartment. The step shall be bright finished, non-skid with a black coating. Each step shall incorporate an LED light to illuminate the stepping surface. The step can be used as a hand hold with two openings wide enough for a gloved hand.</p> <p><u>SWIMMING POOL STYLE LADDER</u></p> <p>A swimming pool style ladder shall be supplied for access to the hosebed on the driver side rear of truck. in place of the standard steps. The ladder shall be constructed of aggressive grip vertical aluminum extrusion, with rubber-covered solid aluminum rungs.</p> <p>Three (3) additional folding steps shall be located three (3) on the driver side front bulkhead. The step(s) shall be bright finished, non-skid with a black coating. Each step shall incorporate an LED light to illuminate the stepping surface. The step(s) can be used as a hand hold with two openings wide enough for a gloved hand.</p> <p><u>PUMP</u></p> <p>Pump shall be a 1500 gpm single (1) stage midship mounted centrifugal type.</p> <p>Pump shall be the class "A" type.</p> <p>Pump shall deliver the percentage of rated discharge at pressures indicated below:</p> <ul style="list-style-type: none"> - 100% of rated capacity at 150 psi net pump pressure. -70% of rated capacity at 200 psi net pump pressure. -50% of rated capacity at 250 psi net pump pressure. <p>Pump body shall be close-grained gray iron, bronze fitted, and horizontally split in two (2) sections for easy removal of the entire impeller shaft assembly (including wear rings).</p> <p>Pump shall be designed for complete servicing from the bottom of the truck, without disturbing the pump setting or apparatus piping.</p> <p>Pump case halves shall be bolted together on a single horizontal face to minimize chance of leakage and facilitate ease of reassembly. No end flanges shall be used.</p>		

	Bidder Complies	
	Yes	No
<p>Discharge manifold of the pump shall be cast as an integral part of the pump body assembly and shall provide a minimum of three (3) 3.50" openings for flexibility in providing various discharge outlets for maximum efficiency.</p> <p>The three (3) 3.50" openings shall be located as follows: one (1) outlet to the right of the pump, one (1) outlet to the left of the pump, and one (1) outlet directly on top of the discharge manifold.</p> <p>Impeller shaft shall be stainless steel, accurately ground to size. It shall be supported at each end by sealed, anti-friction ball bearings for rigid precise support. Impeller shall have flame plated hubs assuring maximum pump life and efficiency despite any presence of abrasive matter in the water supply.</p> <p>Bearings shall be protected from water and sediment by suitable stuffing boxes, flinger rings, and oil seals. No special or sleeve type bearings shall be used.</p> <p><u>PUMP PACKING</u></p> <p>Stuffing boxes shall be of the conventional two (2) piece, split-gland type, to permit adjustment or replacement of Grafoil packing without disturbing the pump. Water shall be fed into stuffing box lantern rings for proper lubrication and cooling when the pump is operating.</p> <p>Lantern rings shall be located at the inner ends of the stuffing boxes, to avoid having to remove them when replacing pump packing.</p> <p>Wear rings shall be bronze and easily replaceable to restore original pump efficiency and eliminate the need to replace the entire pump casing due to wear.</p> <p><u>PUMP TRANSMISSION</u></p> <p>The pump transmission shall be made of a three (3) piece, aluminum, horizontally split casing. Power transfer to pump shall be through a high strength Morse HY-VO silent drive chain. By the use of a chain rather than gears, 50% of the sprocket shall be accepting or transmitting torque, compared to two (2) or three (3) teeth doing all the work.</p> <p>Drive shafts shall be 2.35" diameter hardened and ground alloy steel and supported by ball bearings. The case shall be designed to eliminate the need for water cooling.</p> <p><u>PUMPING MODE</u></p> <p>An interlock system shall be provided to ensure that the pump drive system components are properly engaged so that the apparatus can be safely operated. The interlock system shall be designed to allow stationary pumping only.</p>		

	Bidder Complies	
	Yes	No
<p><u>AIR PUMP SHIFT</u></p> <p>Pump shift engagement shall be made by a two (2) position sliding collar, actuated pneumatically (by air pressure), with a three (3) position air control switch located in the cab. A manual back-up shift control shall also be located on the left side pump panel.</p> <p>Two (2) indicator lights shall be provided adjacent to the pump shift inside the cab. One (1) green light shall indicate the pump shift has been completed and be labeled "pump engaged". The second green light shall indicate when the pump has been engaged, and that the chassis transmission is in pump gear. This indicator light shall be labeled "OK to pump".</p> <p>Another green indicator light shall be installed adjacent to the hand throttle on the pump panel and indicate either the pump is engaged and the road transmission is in pump gear, or the road transmission is in neutral and the pump is not engaged. This indicator light shall be labeled "Warning: Do not open throttle unless light is on".</p> <p>The pump shift shall be interlocked to prevent the pump from being shifted out of gear when the chassis transmission is in gear to meet NFPA requirements.</p> <p>The pump shift control in the cab shall be illuminated to meet NFPA requirements.</p> <p><u>TRANSMISSION LOCK-UP</u></p> <p>The direct gear transmission lock-up for the fire pump operation shall engage automatically when the pump shift control in the cab is activated.</p> <p><u>AUXILIARY COOLING SYSTEM</u></p> <p>A supplementary heat exchange cooling system shall be provided to allow the use of water from the discharge side of the pump for cooling the engine water. Heat exchanger shall be cylindrical type and shall be a separate unit. It shall be installed in the pump or engine compartment with the control located on the pump operator's control panel. Exchanger shall be plumbed to the master drain valve.</p> <p><u>INTAKE RELIEF VALVE</u></p> <p>A relief valve shall be installed on the suction side of the pump preset at 125 psig.</p> <p>Relief valve shall have a working range of 75 psig to 250 psig.</p> <p>Outlet shall terminate below the frame rails with a 2.50" National Standard hose thread adapter and shall have a "do not cap" warning tag.</p> <p>Control shall be located behind an access door at a side pump panel.</p> <p><u>PRESSURE CONTROLLER</u></p> <p>A pressure governor shall be provided.</p>		

	Bidder Complies	
	Yes	No
<p>A pressure transducer shall be installed in the water discharge manifold on the pump.</p> <p>The display panel shall be located at the pump operator's panel.</p> <p><u>PRIMING PUMP</u></p> <p>The priming pump shall be a compressed air powered, high efficiency, multistage venturi based priming system, conforming to standards outlined in the current edition of NFPA 1901.</p> <p>All wetted metallic parts of the priming system are to be of brass and stainless steel construction.</p> <p>One (1) priming control shall open the priming valve and start the pump primer.</p> <p><u>PUMP MANUALS</u></p> <p>There shall be a total of two (2) pump manuals provided by the pump manufacturer and furnished with the apparatus. The manuals shall be provided by the pump manufacturer in the form of two (2) CDs. Each manual shall cover pump operation, maintenance, and parts.</p> <p><u>PLUMBING, STAINLESS STEEL AND HOSE</u></p> <p>All inlet and outlet lines shall be plumbed with either stainless steel pipe, flexible polypropylene tubing or synthetic rubber hose reinforced with hi-tensile polyester braid. All hose's shall be equipped with brass or stainless steel couplings. All stainless steel hard plumbing shall be a minimum of a schedule 10 wall thickness.</p> <p>Where vibration or chassis flexing may damage or loosen piping or where a coupling is required for servicing, the piping shall be equipped with victaulic or rubber couplings.</p> <p>Plumbing manifold bodies shall be ductile cast iron or stainless steel.</p> <p>All piping lines are to be drained through a master drain valve or shall be equipped with individual drain valves. All drain lines shall be extended with a hose to drain below the chassis frame.</p> <p>All water carrying gauge lines shall be of flexible polypropylene tubing.</p> <p>All piping, hose and fittings shall have a minimum of a 500 PSI hydrodynamic pressure rating.</p> <p><u>MAIN PUMP INLETS</u></p> <p>A 6.00" pump manifold inlet shall be provided on each side of the vehicle. The suction inlets shall include screens that are designed to provide cathodic protection for the pump, thus reducing corrosion in the pump.</p> <p><u>MAIN PUMP INLET CAP</u></p> <p>The main pump inlets shall have National Standard Threads with a long handle chrome cap.</p>		

	Bidder Complies	
	Yes	No
<p>The cap shall incorporate a thread design to automatically relieve stored pressure in the line when disconnected (no exception).</p> <p><u>VALVES</u> All discharges shall use in-line ball valves.</p> <p><u>LEFT SIDE INLET</u> There shall be one (1) auxiliary inlet with a 2.50" valve at the left side pump panel, terminating with a 2.50" (F) National Standard hose thread adapter.</p> <p>The auxiliary inlet shall be provided with a strainer, chrome swivel and plug.</p> <p>The location of the valve for the one (1) inlet shall be recessed behind the pump panel.</p> <p><u>INLET CONTROL</u> The side auxiliary inlet(s) shall incorporate a quarter-turn ball valve with the control located at the inlet valve. The valve operating mechanism shall indicate the position of the valve.</p> <p><u>FRONT INLET PROVISION</u> Provisions for a front inlet shall be provided on the passenger side pump suction manifold. Flange shall be capped off for possible addition of front inlet at a later date.</p> <p><u>INLET BLEEDER VALVE</u> A 0.75" bleeder valve shall be provided for each side gated inlet. The valves shall be located behind the panel with a swing style handle control extended to the outside of the panel. The handles shall be chrome plated and provide a visual indication of valve position. The swing handle shall provide an ergonomic position for operating the valve without twisting the wrist and provides excellent leverage. The water discharged by the bleeders shall be routed below the chassis frame rails.</p> <p><u>TANK TO PUMP</u> The booster tank shall be connected to the intake side of the pump with heavy duty piping and a quarter turn 3.00" full flow line valve with the control remotely located at the operator's panel. Tank to pump line shall run straight (no elbows) from the pump into the front face of the water tank and angle down into the tank sump. A rubber coupling shall be included in this line to prevent damage from vibration or chassis flexing.</p> <p>A check valve shall be provided in the tank to pump supply line to prevent the possibility of "back filling" the water tank.</p> <p><u>TANK REFILL</u> A 1.50" combination tank refill and pump re-circulation line shall be provided, using a quarter-turn full flow ball valve controlled from the pump operator's panel.</p>		

	Bidder Complies	
	Yes	No
<p><u>LEFT SIDE DISCHARGE OUTLETS</u></p> <p>There shall be two (2) discharge outlets with a 2.50" valve on the left side of the apparatus, terminating with a 2.50" (M) National Standard hose thread adapter.</p> <p><u>RIGHT SIDE DISCHARGE OUTLETS</u></p> <p>There shall be one (1) discharge outlet with a 2.50" valve on the right side of the apparatus, terminating with a 2.50" (M) National Standard hose thread adapter.</p> <p>There shall be a 4.00" discharge outlet with a 3.00" valve with a 3.00" ball, installed on the right side of the apparatus, terminating with a 4.00" (M) National Standard hose thread adapter. This discharge outlet shall be actuated with a handwheel control with position indicator at the pump operator's control panel.</p> <p><u>FRONT DISCHARGE OUTLET</u></p> <p>There shall be one (1) 1.50" discharge outlet piped to the front of the apparatus and located in the center bumper tray.</p> <p>Plumbing shall consist of 2.00" piping and flexible hose with a 2.00" ball valve with control at the pump operator's panel. A fabricated weldment made of stainless steel pipe shall be used in the plumbing where appropriate. The piping shall terminate with a 1.50" NST with 90 degree stainless steel swivel.</p> <p>There shall be Class 1 automatic drains provided at all low points of the piping.</p> <p><u>REAR DISCHARGE OUTLET</u></p> <p>There shall be one (1) discharge outlet piped to the rear of the hose bed, driver's side, installed so proper clearance is provided for spanner wrenches or adapters. Plumbing shall consist of 2.50" piping along with a 2.50" full flow ball valve with the control from the pump operator's panel.</p> <p><u>DISCHARGE CAPS</u></p> <p>Chrome plated, rocker lug, caps with chains shall be furnished for all side discharge outlets.</p> <p>The cap shall incorporate a thread design to automatically relieve stored pressure in the line when disconnected (no exception).</p> <p><u>OUTLET BLEEDER VALVE</u></p> <p>A 0.75" bleeder valve shall be provided for each outlet 1.50" or larger. Automatic drain valves are acceptable with some outlets if deemed appropriate with the application.</p> <p>The valves shall be located behind the panel with a swing style handle control extended to the outside of the side pump panel. The handles shall be chrome plated and provide a visual indication of valve position. The swing handle shall provide an ergonomic position for operating the valve without twisting the wrist and provides excellent leverage. Bleeders shall be located at</p>		

	Bidder Complies	
	Yes	No
<p>the bottom of the pump panel. They shall be properly labeled identifying the discharge they are plumbed in to. The water discharged by the bleeders shall be routed below the chassis frame rails.</p> <p><u>LEFT SIDE OUTLET EBLAWS</u></p> <p>The two (2) discharge outlets, located on the left side pump panel, shall be furnished with a 2.50" (F) National Standard hose thread x 2.50" (M) CSA, chrome plated, 30 degree elbow.</p> <p>The elbow shall incorporate a thread design to automatically relieve stored pressure in the line when disconnected (no exception).</p> <p><u>RIGHT SIDE OUTLET ELBOWS</u></p> <p>The one (1) discharge outlet, located on the right side pump panel, shall be furnished with a 2.50" (F) National Standard hose thread x 2.50" (M) CSA, chrome plated, 30 degree elbow.</p> <p>The elbow shall incorporate a thread design to automatically relieve stored pressure in the line when disconnected (no exception).</p> <p><u>ADDITIONAL RIGHT SIDE OUTLET ELBOWS</u></p> <p>The 4.00" discharge outlets, located on the right side pump panel, shall be furnished with a 4.00" (F) National Standard hose thread x 4.00" (M) National Standard hose thread, chrome plated, 45 degree elbow with cap.</p> <p><u>REAR OUTLET ELBOWS</u></p> <p>The 2.50" discharge outlets, located at the rear of the apparatus, shall be furnished with a 2.50" (F) National Standard hose thread x 2.50" (M) CSA, chrome plated, 30 degree elbow.</p> <p>The elbow shall incorporate a thread design to automatically relieve stored pressure in the line when disconnected (no exception).</p> <p>Elbows shall be provided for one (1) discharge outlet.</p> <p><u>DISCHARGE OUTLET CONTROLS</u></p> <p>The discharge outlets shall incorporate a quarter-turn ball valve with the control located at the pump operator's panel. The valve operating mechanism shall indicate the position of the valve.</p> <p>If a handwheel control valve is used, the control shall be a minimum of a 3.9" diameter stainless steel handwheel with a dial position indicator built in to the center of the handwheel.</p> <p><u>DELUGE RISER</u></p> <p>A 3.00" deluge riser shall be installed above the pump in such a manner that a monitor can be mounted and used effectively. Piping shall be installed securely so no movement develops when the line is charged. The riser shall be gated and controlled at the pump operator's panel.</p>		

	Bidder Complies	
	Yes	No
<p>The deluge riser shall have male National Pipe Threads for mounting the monitor.</p> <p><u>CROSSLAY HOSE BEDS</u></p> <p>Two (2) crosslays with 1.50" outlets shall be provided. Each bed to be capable of carrying 200' of 1.75" double jacketed hose and shall be plumbed with 2.00" i.d. pipe and gated with a 2.00" quarter turn ball valve.</p> <p>Outlets to be equipped with a 1.50" National Standard hose thread 90 degree swivel located in the hose bed so that hose may be removed from either side of apparatus.</p> <p>The crosslay controls shall be at the pump operator's panel.</p> <p>The center crosslay dividers shall be fabricated of 0.25" aluminum and shall provide adjustment from side to side. The divider shall be unpainted with a brushed finish.</p> <p>Vertical scuffplates constructed of stainless steel shall be provided at the front and rear ends of the bed on each side of vehicle.</p> <p>Crosslay bed flooring shall consist of removable perforated brushed aluminum.</p> <p><u>CROSSLAY/DEADLAY HOSE RESTRAINT</u></p> <p>Elastic netting shall be provided across the top and ends of two (2) crosslay/deadlay opening(s) to secure the hose during travel. The netting shall be permanently attached at the top center of the crosslay/deadlay bed and removable on each end.</p> <p><u>CROSSLAY 8.00" LOWER THAN STANDARD</u></p> <p>The crosslays shall be lowered 8.00" from standard.</p> <p><u>FOAM CONCENTRATE PROPORTIONING SYSTEM PLUMBING (FUTURE INSTALL)</u></p> <p>A foam manifold shall be provided for the future installation of a foam system. The foam system shall be plumbed to for future foam system discharges. The discharges capable of dispensing foam shall be two (2) crosslays and front bumper outlet..</p> <p>A manifold shall be provided for the foam ready discharges. The plumbing from the water pump to the foam manifold shall be designed to allow the foam system to be added without unnecessary rework.</p> <p>Space shall be provided on the pump panel for the possible addition of the foam system controls.</p> <p><u>SINGLE FOAM TANK REFILL</u></p> <p>The foam system's proportioning pump shall be used to fill the foam tank. This shall allow use of the auxiliary foam pick-up to pump the foam from pails or a drum on the ground into the foam tank. A foam shut-off switch shall be installed in the fill dome of the tank to shut the system</p>		

	Bidder Complies	
	Yes	No
<p>down when the tank is full. The fill operation shall be controlled by a mode in the foam system controller. While the proportioner pump is filling the tank, the controller shall display a flashing yellow LED to indicate that the tank is filling. When the tank is full, as determined by the float switch in the tank dome, the pump shall stop and the controller shall shut the yellow LED off. If it attempted to use tank fill and the refill valve and suction valve are in the wrong position(s), then a red LED shall illuminate to indicate the improper valve position(s). When the valves are positioned properly, then filling shall commence.</p> <p><u>FOAM TANK</u></p> <p>The foam tank shall be an integral portion of the polypropylene water tank. The cell shall have a capacity of 20 gallons of foam with the intended use of Class A foam. The foam cell shall not reduce the capacity of the water tank. The foam cell shall have a screen in the fill dome and a breather in the lid.</p> <p><u>FOAM TANK DRAIN</u></p> <p>The foam tank drain shall be a 1.00" drain valve located inside the pump compartment accessible through a door on the passenger's side pump panel.</p> <p><u>PUMP COMPARTMENT</u></p> <p>The pump compartment shall be separate from the hose body and compartments so that each may flex independently of the other. It shall be a fabricated assembly of steel tubing, angles and channels which supports both the fire pump and the side running boards.</p> <p>The pump compartment shall be mounted on the chassis frame rails with rubber biscuits in a four point pattern to allow for chassis frame twist.</p> <p>Pump compartment, pump, plumbing and gauge panels shall be removable from the chassis in a single assembly.</p> <p><u>PUMP MOUNTING</u></p> <p>Pump shall be mounted to a substructure which shall be mounted to the chassis frame rail using rubber isolators. The mounting shall allow chassis frame rails to flex independently without damage to the fire pump.</p> <p><u>LEFT SIDE PUMP CONTROL PANELS</u></p> <p>All pump controls and gauges shall be located at the left (driver's) side of the apparatus and properly identified.</p> <p>Layout of the pump control panel shall be ergonomically efficient and systematically organized.</p> <p>The pump operator's control panel shall be removable in two (2) main sections for ease of maintenance:</p>		

	Bidder Complies	
	Yes	No
<p>The upper section shall contain sub panels for the mounting of the pump pressure control device, engine monitoring gauges, electrical switches, and foam controls (if applicable). Sub panels shall be removable from the face of the pump panel for ease of maintenance. Below the sub panels shall be located all valve controls and line pressure gauges.</p> <p>The lower section of the panel shall contain all inlets, outlets, and drains.</p> <p>All push/pull valve controls shall have 1/4 turn locking control rods with polished chrome plated zinc tee handles. Guides for the push/pull control rods shall be chrome plated zinc castings securely mounted to the pump panel. Push/pull valve controls shall be capable of locking in any position. The control rods shall pull straight out of the panel and shall be equipped with universal joints to eliminate binding.</p> <p><u>IDENTIFICATION TAGS</u></p> <p>The identification tag for each valve control shall be recessed in the face of the tee handle.</p> <p>All discharge outlets shall have color coded identification tags, with each discharge having its own unique color. Color coding shall include the labeling of the outlet and the drain for each corresponding discharge.</p> <p>All line pressure gauges shall be mounted directly above the corresponding discharge control tee handles and recessed within the same chrome plated casting as the rod guide for quick identification. The gauge and rod guide casting shall be removable from the face of the pump panel for ease of maintenance. The casting shall be color coded to correspond with the discharge identification tag.</p> <p>All remaining identification tags shall be mounted on the pump panel in chrome plated bezels.</p> <p>The pump panel on the right (passenger's) side shall be removable with lift and turn type fasteners.</p> <p>Trim rings shall be installed around all inlets and outlets.</p> <p>The trim rings for the side discharge outlets shall be color coded and labeled to correspond with the discharge identification tag.</p> <p><u>PUMP PANEL CONFIGURATION</u></p> <p>The pump panel configuration shall be arranged and installed in an organized manner that shall provide user-friendly operation.</p> <p><u>PUMP AND GAUGE PANEL</u></p> <p>The pump and gauge panels shall be constructed of aluminum with a black vinyl finish. A polished aluminum trim molding shall be provided around each panel.</p>		

	Bidder Complies	
	Yes	No
<p>The passenger's side pump panel shall be removable and fastened with swell type fasteners.</p> <p><u>PUMP COMPARTMENT LIGHT</u></p> <p>There shall be one (1) 3.00" white 12 volt DC LED light(s) with flange(s) installed in the pump compartment.</p> <p>There shall be a switch accessible through a door on the pump panel included with this installation.</p> <p>Engine monitoring graduated LED indicators shall be incorporated with the pressure controller.</p> <p>Also provided at the pump panel shall be the following:</p> <ul style="list-style-type: none"> - Master Pump Drain Control <p><u>VACUUM AND PRESSURE GAUGES</u></p> <p>The pump vacuum and pressure gauges shall be liquid filled.</p> <p>The gauges shall be a minimum of 4.00" in diameter and shall have white faces with black markings, with a pressure range of 30.00" 0-400 psi/kpa.</p> <p>Gauge construction shall include a Zytel nylon case with adhesive mounting gasket and threaded retaining nut.</p> <p>The pump pressure and vacuum gauges shall be installed adjacent to each other at the pump operator's control panel.</p> <p>Test port connections shall be provided at the pump operator's panel. One (1) shall be connected to the intake side of the pump, and the other to the discharge manifold of the pump. They shall have 0.25 in. standard pipe thread connections and non-corrosive polished stainless steel or brass plugs. They shall be marked with a label.</p> <p>This gauge shall include a 10 year warranty against leakage, pointer defect, and defective bourdon tube.</p> <p><u>PRESSURE GAUGES</u></p> <p>The individual "line" pressure gauges for the discharges shall be fluid filled.</p> <p>They shall be a minimum of 2.00" in diameter and the dial shall have white faces with black markings.</p> <p>Gauge construction shall include a Zytel nylon case with adhesive mounting gasket and threaded retaining nut.</p> <p>Gauges shall have a pressure rating of 0-400 psi/kpa.</p>		

	Bidder Complies	
	Yes	No
<p>The individual pressure gauge shall be installed as close to the outlet control as practical.</p> <p>This gauge shall include a 10 year warranty against leakage, pointer defect, and defective bourdon tube.</p> <p><u>WATER LEVEL GAUGE</u></p> <p>There shall be an electronic water level gauge provided on the operator's panel that registers water level by means of five (5) colored LED lights. The lights shall be durable, ultra-bright five (5) LED design viewable through 180 degrees. The water level indicators shall be as follows:</p> <ul style="list-style-type: none"> • 100 percent = Green • 75 percent = Yellow • 50 percent = Yellow • 25 percent = Yellow • Refill = Red <p>The light shall flash when the level drops below the given level indicator to provide an eighth of a tank indication. To further alert the pump operator, the lights shall flash sequentially when the water tank is empty.</p> <p>The level measurement shall be based on the sensing of head pressure of the fluid in the tank.</p> <p>The display shall be constructed of a solid plastic material with a chrome plated die cast bezel to reduce vibrations that can cause broken wires and loose electronic components. The encapsulated design shall provide complete protection from water and environmental elements. An industrial pressure transducer shall be mounted to the outside of the tank. The field calibratable display measures head pressure to accurately show the tank level.</p> <p><u>FOAM LEVEL GAUGE</u></p> <p>An electronic foam level gauge shall be provided on the operator's panel that registers foam level by means of five (5) colored LED lights. The lights shall be durable, ultra-bright five (5) LED design viewable through 180 degrees. The foam level indicators shall be as follows:</p> <ul style="list-style-type: none"> • 100 percent = Green • 75 percent = Yellow • 50 percent = Yellow • 25 percent = Yellow • Refill = Red <p>The light shall flash when the level drops below the given level indicator to provide an eighth of a tank indication. To further alert the pump operator, the lights shall flash sequentially when the foam tank is empty.</p>		

	Bidder Complies	
	Yes	No
<p>The level measurement shall be based on the sensing of head pressure of the fluid in the tank.</p> <p>The display shall be constructed of a solid plastic material with a chrome plated die cast bezel to reduce vibrations that can cause broken wires and loose electronic components. The encapsulated design shall provide complete protection from foam and environmental elements. An industrial pressure transducer shall be mounted to the outside of the tank. The display shall be able to be calibrated in the field and shall measure head pressure to accurately show the tank level.</p> <p><u>LIGHT SHIELD</u></p> <p>There shall be a polished, 16 gauge stainless steel light shield installed over the pump operator's panel.</p> <ul style="list-style-type: none"> • There shall be 12 volt DC white LED lights installed under the stainless steel light shield to illuminate the controls, switches, essential instructions, gauges, and instruments necessary for the operation of the apparatus. These lights shall be activated by the pump panel light switch. Additional lights shall be included every 18.00" depending on the size of the pump house. • One (1) pump panel light shall come on when the pump is in ok to pump mode. <p>There shall be a light activated above the pump panel light switch when the parking brake is set. This is to afford the operator some illumination when first approaching the control panel.</p> <p>There shall be a green pump engaged indicator light activated on at the operator's panel when the pump is shifted into gear from inside the cab.</p> <p><u>AIR HORN SYSTEM</u></p> <p>There shall be two (2) air horns recessed in the front bumper. The horn system shall be piped to the air brake system wet tank utilizing 0.38" tubing. A pressure protection valve shall be installed in-line to prevent loss of air in the air brake system.</p> <p><u>Air Horn Location</u></p> <p>The air horns shall be located on each side of the bumper, towards the outside.</p> <p><u>AIR HORN CONTROL</u></p> <p>The air horns shall be actuated by a chrome push button located on the officer's side of the engine tunnel and by the horn button in the steering wheel. The driver shall have the option to control the air horns or the chassis horns from the horn button by means of a selector switch located on the instrument panel.</p> <p><u>ELECTRONIC SIREN</u></p> <p>An electronic siren with noise canceling microphone shall be provided.</p>		

	Bidder Complies	
	Yes	No
<p>This siren to be active when the battery switch is on and that emergency master switch is on.</p> <p>Electronic siren head shall be located in the center console.</p> <p>Siren to be actuated by one (1) foot switch located on the officer's side.</p> <p><u>SPEAKER</u></p> <p>There shall be one (1) speaker provided. Each speaker shall be a black nylon composite, 100-watt, with through bumper mounting brackets and polished stainless steel grille. Each speaker shall be connected to the siren amplifier.</p> <p>The speaker(s) shall be recessed in the front bumper on the driver's side.</p> <p><u>FRONT ZONE UPPER WARNING LIGHTS</u></p> <p>There shall be one (1) 60.00" LED lightbar mounted on the cab roof.</p> <p>The lightbar shall include the following:</p> <ul style="list-style-type: none"> • One (1) red flashing LED module in the driver's side rear corner position. • Open in the driver's side end position. • One (1) red flashing LED module in the driver's side front corner position. • One (1) red flashing LED module in the driver's side first front position. • Open in the driver's side second front position. • Open in the driver's side third front position. • Open in the driver's side fourth front position. • One (1) red flashing LED module in the driver's side fifth front position. • One (1) red flashing LED module in the passenger's side fifth front position. • Open in the passenger's side fourth front position. • Open in the passenger's side third front position. • Open in the passenger's side second front position. • One (1) red flashing LED module in the passenger's side first front position. • One (1) red flashing LED module in the passenger's side front corner position. • Open in the passenger's side end position. • One (1) red flashing LED module in the passenger's side rear corner position. <p>There shall be clear lenses included on the lightbar.</p> <p>There shall be a switch in the cab on the switch panel to control this lightbar.</p> <p>The four (4) red flashing LED modules in the front positions may be load managed when the parking brake is applied.</p>		

	Bidder Complies	
	Yes	No
<p><u>FRONT ZONE LOWER LIGHTS</u></p> <p>There shall be one (1) pair of flashing LED lights installed on the cab face above the headlights, in a common bezel with the directional lights.</p> <p>The color of these lights shall be red Super LED/clear lens.</p> <p>There shall be a switch located in the cab on the switch panel to control the lights..</p> <p><u>HEADLIGHT FLASHER</u></p> <p>The high beam headlights shall flash alternately between the left and right side.</p> <p>There shall be a switch installed in the cab on the switch panel to control the high beam flash. This switch shall be live when the battery switch and the emergency master switches are on.</p> <p>The flashing shall automatically cancel when the hi-beam headlight switch is activated or when the parking brake is set.</p> <p><u>SIDE ZONE LOWER LIGHTING</u></p> <p>There shall be four (4) flashing LED warning lights installed per the following:</p> <ul style="list-style-type: none"> • Two (2) lights, one (1) each side on the bumper extension. The side front lights to include red LEDs with clear lenses. • Two (2) lights, one (1) each side above rear wheels. The rear lights to include red LEDs with clear lenses. <p>There shall be a switch in the cab on the switch panel to control the lights.</p> <p><u>REAR ZONE LOWER LIGHTING</u></p> <p>There shall be two (2) 6 x 4 red Super LED/clear lens lights located at the rear of the apparatus.</p> <p>Each light shall be mounted in a housing.</p> <p>There shall be a switch located in the cab on the switch panel to control the lights.</p> <p><u>REAR/SIDE ZONE UPPER WARNING LIGHTS</u></p> <p>There shall be four (4) LED light with chrome flanges provided.</p> <ul style="list-style-type: none"> • The side rear upper light(s) on the driver's side to be red. • The rear upper light(s) on the driver's side to be red. • The rear upper light(s) on the passenger's side to be red. • The side rear upper light(s) on the passenger's side to be red. <p>The color of the lenses shall be clear.</p>		

	Bidder Complies	
	Yes	No
<p>There shall be a switch located in the cab on the switch panel to control the lights.</p> <p><u>LOOSE EQUIPMENT</u></p> <p>The following equipment shall be furnished with the completed unit:</p> <p>- One (1) bag of chrome, stainless steel, or cadmium plated screws, nuts, bolts and washers, as used in the construction of the unit</p> <p><u>NFPA REQUIRED LOOSE EQUIPMENT PROVIDED BY FIRE DEPARTMENT</u></p> <p>The following loose equipment as outlined in NFPA 1901, 2016 edition, section 5.9.3 and 5.9.4 shall be provided by the fire department.</p> <ul style="list-style-type: none"> • 800 ft (60 m) of 2.50" (65 mm) or larger fire hose. • 400 ft (120 m) of 1.50" (38 mm), 1.75" (45 mm), or 2.00" (52 mm) fire hose. • One (1) handline nozzle, 200 gpm (750 L/min) minimum. • Two (2) handline nozzles, 95 gpm (360 L/min) minimum. • One (1) smoothbore or combination nozzle with 2.50" shutoff that flows a minimum of 250 gpm. • One (1) SCBA complying with NFPA 1981 for each assigned seating position, but not fewer than four (4), mounted in brackets fastened to the apparatus or stored in containers supplied by the SCBA manufacturer. • One (1) spare SCBA cylinder for each SCBA carried, each mounted in a bracket fastened to the apparatus or stored in a specially designed storage space(s). • One (1) first aid kit. • Four (4) combination spanner wrenches. • Two (2) hydrant wrenches. • One (1) double female 2.50" (65 mm) adapter with National Hose threads. • One (1) double male 2.50" (65 mm) adapter with National Hose threads. • One (1) rubber mallet, for use on suction hose connections. • Two (2) salvage covers each a minimum size of 12 ft x 14 ft (3.7 m x 4.3 m). • One (1) traffic vest for each seating position, each vest to comply with ANSI/ISEA 207, <i>Standard for High Visibility Public Safety Vests</i>, and have a five-point breakaway feature that includes two (2) at the shoulders, two (2) at the sides, and one (1) at the front. • Five (5) fluorescent orange traffic cones not less than 28.00" (711 mm) in height, each equipped with a 6.00" (152 mm) retro-reflective white band no more than 4.00" (152 mm) from the top of the cone, and an additional 4.00" (102 mm) retro-reflective white band 2.00" (51 mm) below the 6.00" (152 mm) band. • Five (5) illuminated warning devices such as highway flares, unless the five (5) fluorescent orange traffic cones have illuminating capabilities. • One (1) automatic external defibrillator (AED). 		

	Bidder Complies	
	Yes	No
<ul style="list-style-type: none"> • Four (4) ladder belts meeting the requirements of NFPA 1983, <i>Standard on Fire Service Life Safety Rope and System Components</i> (if equipped with an aerial device). • If the supply hose carried does not use sexless couplings, an additional double female adapter and double male adapter, sized to fit the supply hose carried, shall be carried mounted in brackets fastened to the apparatus. • If none of the pump intakes are valved, a hose appliance that is equipped with one or more gated intakes with female swivel connection(s) compatible with the supply hose used on one side and a swivel connection with pump intake threads on the other side shall be carried. Any intake connection larger than 3.00" (75 mm) shall include a pressure relief device that meets the requirements of 16.6.6. • If the apparatus does not have a 2.50" National Hose (NH) intake, an adapter from 2.50" NH female to a pump intake shall be carried, mounted in a bracket fastened to the apparatus if not already mounted directly to the intake. • If the supply hose carried has other than 2.50" National Hose (NH) threads, adapters shall be carried to allow feeding the supply hose from a 2.50" NH thread male discharge and to allow the hose to connect to a 2.50" NH female intake, mounted in brackets fastened to the apparatus if not already mounted directly to the discharge or intake. <p><u>SOFT SUCTION HOSE PROVIDED BY DEALER</u> NFPA 1901, 2016 edition, section 5.8.2.1 requires a minimum of 20' of suction hose or 15' of supply hose shall be carried.</p> <p>Hose is not on the apparatus as manufactured. The dealer shall provide suction or supply hose.</p> <p><u>DRY CHEMICAL EXTINGUISHER PROVIDED BY FIRE DEPARTMENT</u> NFPA 1901, 2016 edition, section 5.9.4 requires one (1) approved dry chemical portable fire extinguisher with a minimum 80-B:C rating mounted in a bracket fastened to the apparatus.</p> <p>The extinguisher is not on the apparatus as manufactured. The fire department shall provide and mount the extinguisher.</p> <p><u>WATER EXTINGUISHER PROVIDED BY FIRE DEPARTMENT</u> NFPA 1901, 2016 edition, section 5.9.4 requires one (1) 2.5 gallon or larger water extinguisher mounted in a bracket fastened to the apparatus.</p> <p>The extinguisher is not on the apparatus as manufactured. The fire department shall provide and mount the extinguisher.</p> <p><u>FLATHEAD AXE PROVIDED BY FIRE DEPARTMENT</u> NFPA 1901, 2016 edition, Section 5.9.4 requires one (1) flathead axe mounted in a bracket fastened to the apparatus.</p>		

	Bidder Complies	
	Yes	No
<p>The axe is not on the apparatus as manufactured. The fire department shall provide and mount the axe.</p> <p><u>PICKHEAD AXE PROVIDED BY FIRE DEPARTMENT</u></p> <p>NFPA 1901, 2016 edition, Section 5.9.4 requires one (1) pickhead axe mounted in a bracket fastened to the apparatus.</p> <p>The axe is not on the apparatus as manufactured. The fire department shall provide and mount the axe.</p> <p><u>PAINT PROCESS</u></p> <p>The exterior custom cab and/or body painting procedure shall consist of a seven (7) step finishing process. A commercial chassis paint process shall follow similar processes as determined by the chassis manufacturer. The following procedure shall be used by the apparatus manufacturer:</p> <ol style="list-style-type: none"> 1. <u>Manual Surface Preparation</u> - All exposed metal surfaces on the custom cab and body shall be thoroughly cleaned and prepared for painting. Imperfections on the exterior surfaces shall be removed and sanded to a smooth finish. Exterior seams shall be sealed before painting. Exterior surfaces that shall not be painted include; chrome plating, polished stainless steel, anodized aluminum and bright aluminum treadplate. 2. <u>Chemical Cleaning and Pretreatment</u> - All surfaces shall be chemically cleaned to remove dirt, oil, grease, and metal oxides to ensure the subsequent coatings bond well. The aluminum surfaces shall be properly cleaned and treated using a high pressure, high temperature 4 step Acid Etch process. The steel and stainless surfaces shall be properly cleaned and treated using a high temperature 3 step process specifically designed for steel or stainless. The chemical treatment converts the metal surface to a passive condition to help prevent corrosion. A final pure water rinse shall be applied to all metal surfaces. 3. <u>Surfacer Primer</u> - The Surfacer Primer shall be applied to a chemically treated metal surface to provide a strong corrosion protective base coat. A minimum thickness of 2 mils of Surfacer Primer is applied to surfaces that require a critical aesthetic finish. The surfacer primer shall be a two-component high solids urethane that has excellent sanding properties and an extra smooth finish when sanded. 4. <u>Finish Sanding</u> - The surfacer primer shall be sanded with a fine grit abrasive to achieve an ultra-smooth finish. This sanding process is critical to produce the smooth mirror like finish in the topcoat. 5. <u>Sealer Primer</u> - The sealer primer is applied prior to the base coat in all areas that have not been previously primed with the surfacer primer. The sealer primer is a two-component high solids urethane that goes on smooth and provides excellent gloss hold out when top coated. 		

	Bidder Complies	
	Yes	No
<p>6. <u>Base coat Paint</u> - Two coats of a high performance, two component high solids polyurethane base coat shall be applied. The Base coat shall be applied to a thickness that shall achieve the proper color match. The Base coat shall be used in conjunction with a urethane clear coat to provide protection from the environment.</p> <p>7. <u>Clear Coat</u> - Two (2) coats of clear coat shall be applied over the base coat color. The clear coat is a two-component high solids urethane that provides superior gloss and durability to the exterior surfaces. Lap style doors shall be clear coated to match the body. Paint warranty for the roll-up doors shall be provided by the roll-up door manufacturer.</p> <p>Specifications are written to define cyclic corrosion testing, physical strengths, durability and minimum appearance requirements must be met in order for an exterior paint finish to be considered acceptable as a quality finish.</p> <p>Each batch of base coat color shall be checked for a proper match before painting of the cab and the body. After the cab and body are painted, the color is verified again to make sure that it matches the color standard. Electronic color measuring equipment shall be used to compare the color sample to the color standard entered into the computer. Color specifications are used to determine the color match. A Delta E reading shall be used to determine a good color match within each family color.</p> <p>All removable items such as brackets, compartment doors, door hinges, and trim shall be removed and separately if required, to ensure paint behind all mounted items. Body assemblies that cannot be finish painted after assembly shall be finish painted before assembly.</p> <p><u>PAINT - ENVIRONMENTAL IMPACT</u></p> <p>Contractor shall meet or exceed all current State regulations concerning paint operations. Pollution control shall include measures to protect the atmosphere, water and soil. Controls shall include the following conditions:</p> <ul style="list-style-type: none"> • Topcoats and primers shall be chrome and lead free. • Metal treatment chemicals shall be chrome free. The wastewater generated in the metal treatment process shall be treated on-site to remove any other heavy metals. • Particulate emission collection from sanding operations shall have a 99.99% efficiency factor. • Particulate emissions from painting operations shall be collected by a dry filter or water wash process. If the dry filter is used, it shall have an efficiency rating of 98.00%. Water wash systems shall be 99.97% efficient • Water from water wash booths shall be reused. Solids shall be removed on a continual basis to keep the water clean. • Paint wastes shall be disposed of in an environmentally safe manner. 		

	Bidder Complies	
	Yes	No
<ul style="list-style-type: none"> • Empty metal paint containers shall be recycled to recover the metal. • Solvents used in clean-up operations shall be recycled on-site or sent off-site for distillation and returned for reuse. <p>Additionally, the finished apparatus shall not be manufactured with or contain products that have ozone depleting substances. Contractor shall, upon demand, present evidence that the manufacturing facility meets the above conditions and that it is in compliance with the state EPA rules and regulations.</p> <p><u>PAINT</u> The cab and the body shall be painted #90 red</p> <p><u>PAINT CHASSIS FRAME ASSEMBLY</u> The chassis frame assembly shall be painted black before the installation of the cab and body, and before installation of the engine and transmission assembly, air brake lines, electrical wire harnesses, etc.</p> <p>Components treated with epoxy E-coat protection prior to paint:</p> <ul style="list-style-type: none"> • Two (2) C-channel frame rails <p>Components that are included with the chassis frame assembly that shall be painted not e-coated are:</p> <ul style="list-style-type: none"> • Cross members • Axles • Suspensions • Steering gear • Battery boxes • Bumper extension weldment • Frame extensions • Body mounting angles • Rear Body support substructure (front and rear) • Pump house substructure • Air tanks • Fuel tank • Castings • Individual piece parts used in chassis and body assembly <p>The E-coat process shall meet the technical properties shown.</p>		

	Bidder Complies	
	Yes	No
<p><u>COMPARTMENT INTERIOR PAINT</u> The interior of compartmentation shall be painted with a gray spatter type paint.</p> <p><u>REFLECTIVE STRIPES</u> Three (3) reflective stripes shall be provided across the front of the vehicle and along the sides of the body. The reflective band shall consist of a 1.00" white stripe at the top with a 1.00" gap then a 6.00" white stripe with a 1.00" gap and a 1.00" white stripe on the bottom.</p> <p><u>REFLECTIVE STRIPE ON CAB FACE</u> The reflective band provided on the cab face shall be located below the stainless steel trim band and above the front bumper.</p> <p><u>REAR CHEVRON STRIPING</u> There shall be alternating chevron striping located on the rear-facing vertical surface of the apparatus. The rear surface, excluding the rear compartment door, shall be covered. The colors shall be red and fluorescent yellow green diamond grade. Each stripe shall be 6.00" in width. This shall meet the requirements of the current edition of NFPA 1901, which states that 50% of the rear surface shall be covered with chevron striping.</p> <p><u>CAB DOOR REFLECTIVE STRIPE</u> A 6.00" x 16.00" fluorescent yellow green diamond grade reflective stripe shall be provided across the interior of each cab door. The stripe shall be located approximately 1.00" up from the bottom, on the door panel. This stripe shall meet the NFPA 1901 requirement.</p> <p><u>FIRE APPARATUS PARTS CD MANUAL</u> There shall be two (2) custom parts manuals for the complete fire apparatus provided in CD format with the completed unit. The manuals shall contain the following:</p> <ul style="list-style-type: none"> • Job number • Part numbers with full descriptions • Table of contents • Parts section sorted in functional groups reflecting a major system, component, or assembly • Parts section sorted in alphabetical order • Instructions on how to locate parts 		

	Bidder Complies	
	Yes	No
<p>The manuals shall be specifically written for the chassis and body model being purchased. It shall not be a generic manual for a multitude of different chassis and bodies.</p> <p><u>SERVICE PARTS INTERNET SITE</u></p> <p>The service parts information included in these manuals are also available on the factory website. The website offers additional functions and features not contained in this manual, such as digital photographs and line drawings of select items. The website also features electronic search tools to assist in locating parts quickly.</p> <p><u>CHASSIS SERVICE CD MANUALS</u></p> <p>There shall be two (2) CD format chassis service manuals containing parts and service information on major components provided with the completed unit.</p> <p>The manual shall contain the following sections:</p> <ul style="list-style-type: none"> • Job number • Table of contents • Troubleshooting • Front Axle/Suspension • Brakes • Engine/Tires • Wheels • Cab • Electrical, DC • Air Systems • Plumbing • Appendix <p>The manual shall be specifically written for the chassis model being purchased. It shall not be a generic manual for a multitude of different chassis and bodies.</p> <p><u>CHASSIS OPERATION CD MANUALS</u></p> <p>There shall be two (2) CD format chassis operation manuals provided.</p> <p><u>ONE (1) YEAR MATERIAL AND WORKMANSHIP</u></p> <p>Each new piece of apparatus shall be provided with a minimum one (1) year basic apparatus material and workmanship limited warranty. The warranty shall cover such portions of the apparatus built by the manufacturer as being free from defects in material and workmanship that would arise under normal use and service.</p> <p>A copy of the warranty certificate shall be submitted with the bid package (no exception).</p>		

	Bidder Complies	
	Yes	No
<p><u>ENGINE WARRANTY</u> A five (5) year limited engine warranty shall be provided. A copy of the warranty certificate shall be submitted with the bid package.</p> <p><u>STEERING GEAR WARRANTY</u> A one (1) year limited steering gear warranty shall be provided. A copy of the warranty certificate shall be submitted with the bid package.</p> <p><u>FIFTY (50) YEAR STRUCTURAL INTEGRITY</u> The chassis frame shall be provided with a fifty (50) year material and workmanship limited warranty. The warranty shall cover the chassis frame as being free from defects in material and workmanship that would arise under normal use and service. A copy of the warranty certificate shall be submitted with the bid package (no exception).</p> <p><u>FRONT AXLE WARRANTY</u> A five (5)-year/100,000 mile parts and labor warranty shall be provided.</p> <p><u>REAR AXLE WARRANTY</u> A five (5)-year/100,000 mile parts and labor warranty shall be provided.</p> <p><u>BRAKE SYSTEM THREE (3) YEAR MATERIAL AND WORKMANSHIP WARRANTY</u> A three (3) year brake system limited warranty shall be provided.</p> <p><u>TEN (10) YEAR STRUCTURAL INTEGRITY</u> The new cab shall be provided with a ten (10) year material and workmanship limited warranty. The warranty shall cover such portions of the cab built by the manufacturer as being free from structural failures caused by defects in material and workmanship that would arise under normal use and service. A copy of the warranty certificate shall be submitted with the bid package (no exception).</p> <p><u>TEN (10) YEAR PRO-RATED PAINT AND CORROSION</u> Each new piece of apparatus shall be provided with a ten (10) year pro-rated paint and corrosion limited warranty on the apparatus cab. The warranty shall cover painted exterior surfaces of the body to be free from blistering, peeling, corrosion, or any other adhesion defect caused by defective manufacturing methods or paint material selection that would arise under normal use and service. A copy of the warranty certificate shall be submitted with the bid package (no exception).</p> <p><u>CAMERA SYSTEM WARRANTY</u> A four (4) month warranty shall be provided for the camera system.</p>		

	Bidder Complies	
	Yes	No
<p><u>COMPARTMENT LIGHT WARRANTY</u></p> <p>A ten (10) year material and workmanship limited warranty shall be provided for the Pierce 12 volt DC LED strip lights. The warranty shall cover the LED strip lights to be free from defects in material and workmanship that would arise under normal use.</p> <p>A copy of the warranty certificate shall be submitted with the bid package (no exception).</p> <p><u>TRANSMISSION WARRANTY</u></p> <p>The transmission shall have a five (5) year/unlimited mileage warranty covering 100 percent parts and labor. The warranty is to be provided by transmission supplier and not the apparatus builder.</p> <p><u>TRANSMISSION COOLER WARRANTY</u></p> <p>The transmission cooler shall carry a five (5) year parts and labor warranty (exclusive to the transmission cooler). In addition, a collateral damage warranty shall also be in effect for the first three (3) years of the warranty coverage and shall not exceed \$10,000 per occurrence. A copy of the warranty certificate shall be submitted with the bid package.</p> <p><u>WATER TANK WARRANTY</u></p> <p>The poly water tank shall be provided with a lifetime material and workmanship limited warranty.</p> <p>A copy of the warranty certificate shall be submitted with the bid package (no exception).</p> <p><u>TEN (10) YEAR STRUCTURAL INTEGRITY</u></p> <p>Each new piece of apparatus shall be provided with a ten (10) year material and workmanship limited warranty on the apparatus body. The warranty shall cover such portions of the apparatus built by the manufacturer as being free from defects in material and workmanship that would arise under normal use and service.</p> <p>A copy of the warranty certificate shall be submitted with the bid package (no exception).</p> <p><u>ROLL UP DOOR MATERIAL AND WORKMANSHIP WARRANTY</u></p> <p>A roll-up door limited warranty shall be provided. The mechanical components of the roll-up door shall be warranted against defects in material and workmanship for the lifetime of the vehicle. A six (6) year limited warranty shall be provided on painted and satin roll up doors.</p> <p>A copy of the warranty certificate shall be submitted with the bid package.</p> <p><u>PUMP WARRANTY</u></p> <p>The pump shall be provided with a five (5) year material and workmanship limited warranty.</p> <p>A copy of the warranty certificate shall be submitted with the bid package (no exception).</p>		

	Bidder Complies	
	Yes	No
<p><u>TEN (10) YEAR PUMP PLUMBING WARRANTY</u></p> <p>The stainless steel plumbing components and ancillary brass fittings used in the construction of the water/foam plumbing system shall be warranted for a period of ten (10) years or 100,000 miles. This covers structural failures caused by defective design or workmanship, or perforation caused by corrosion, provided the apparatus is used in a normal and reasonable manner. This warranty is extended only to the original purchaser for a period of ten years from the date of delivery.</p> <p>A copy of the warranty certificate shall be submitted with the bid package (no exception).</p> <p><u>TEN (10) YEAR PRO-RATED PAINT AND CORROSION</u></p> <p>Each new piece of apparatus shall be provided with a ten (10) year pro-rated paint and corrosion limited warranty on the apparatus body. The warranty shall cover painted exterior surfaces of the body to be free from blistering, peeling, corrosion, or any other adhesion defect caused by defective manufacturing methods or paint material selection that would arise under normal use and service.</p> <p>A copy of the warranty certificate shall be submitted with the bid package (no exception).</p> <p><u>VEHICLE STABILITY CERTIFICATION</u></p> <p>The fire apparatus manufacturer shall provide a certification stating the apparatus complies with NFPA 1901, current edition, section 4.13, Vehicle Stability. The certification shall be provided at the time of bid.</p> <p><u>ENGINE INSTALLATION CERTIFICATION</u></p> <p>The fire apparatus manufacturer shall provide a certification, along with a letter from the engine manufacturer stating they approve of the engine installation in the bidder's chassis. The certification shall be provided at the time of bid.</p> <p><u>POWER STEERING CERTIFICATION</u></p> <p>The fire apparatus manufacturer shall provide a certification stating the power steering system as installed meets the requirements of the component supplier. The certification shall be provided at the time of bid.</p> <p><u>CAB INTEGRITY CERTIFICATION</u></p> <p>The fire apparatus manufacturer shall provide a cab crash test certification with this proposal. Testing shall meet or exceed the requirements below:</p> <ul style="list-style-type: none"> - European Occupant Protection Standard ECE Regulation No.29. - SAE J2422 Cab Roof Strength Evaluation - Quasi-Static Loading Heavy Trucks. - SAE J2420 COE Frontal Strength Evaluation - Dynamic Loading Heavy Trucks. 		

	Bidder Complies	
	Yes	No
<p>There shall be no exception to any portion of the cab integrity certification. Nonconformance shall lead to immediate rejection of bid.</p> <p><u>CAB DOOR DURABILITY CERTIFICATION</u></p> <p>Robust cab doors help protect occupants. Cab doors shall survive a 200,000 cycle door slam test where the slamming force exceeds 20 G's of deceleration. The bidder shall certify that the sample doors similar to those provided on the apparatus have been tested and have met these criteria without structural damage, latch malfunction, or significant component wear.</p> <p><u>WINDSHIELD WIPER DURABILITY CERTIFICATION</u></p> <p>Visibility during inclement weather is essential to safe apparatus performance. Windshield wipers shall survive a 3 million cycle durability test in accordance with section 6.2 of SAE J198 <i>Windshield Wiper Systems - Trucks, Buses and Multipurpose Vehicles</i>. The bidder shall certify that the wiper system design has been tested and that the wiper system has met these criteria.</p> <p><u>SEAT BELT ANCHOR STRENGTH</u></p> <p>Seat belt attachment strength is regulated by Federal Motor Vehicle Safety Standards and should be validated through testing. Each seat belt anchor design shall withstand 3000 lb of pull on both the lap and shoulder belt in accordance with FMVSS 571.210 Seat Belt Assembly Anchorages. The bidder shall certify that each anchor design was pull tested to the required force and met the appropriate criteria.</p> <p><u>SEAT MOUNTING STRENGTH</u></p> <p>Seat attachment strength is regulated by Federal Motor Vehicle Safety Standards and should be validated through testing. Each seat mounting design shall be tested to withstand 20 G's of force in accordance with FMVSS 571.207 Seating Systems. The bidder shall certify, at time of delivery, that each seat mount and cab structure design was pull tested to the required force and met the appropriate criteria.</p> <p><u>CAB DEFROSTER CERTIFICATION</u></p> <p>Visibility during inclement weather is essential to safe apparatus performance. The defroster system shall clear the required windshield zones in accordance with SAE J381 Windshield Defrosting Systems Test Procedure and Performance Requirements - Trucks, Buses, and Multipurpose Vehicles. The bidder shall certify that the defrost system design has been tested in a cold chamber and passes the SAE J381 criteria.</p> <p><u>CAB HEATER CERTIFICATION</u></p> <p>Good cab heat performance and regulation provides a more effective working environment for personnel, whether in-transit, or at a scene. The cab heaters shall warm the cab 77 degrees Fahrenheit from a cold-soak, within 30 minutes when tested using the coolant supply methods</p>		

Bidder Complies	
Yes	No

found in SAE J381. The bidder shall certify, at time of delivery, that a substantially similar cab has been tested and has met these criteria.

CAB AIR CONDITIONING PERFORMANCE CERTIFICATION

Good cab air conditioning temperature and air flow performance keeps occupants comfortable, reduces humidity, and provides a climate for recuperation while at the scene. The cab air conditioning system shall cool the cab from a heat-soaked condition at 100 degrees Fahrenheit to an average of 78 degrees Fahrenheit in 30 minutes. The bidder shall certify that a substantially similar cab has been tested and has met these criteria.

AMP DRAW REPORT

The bidder shall provide, at the time of bid and delivery, an itemized print out of the expected amp draw of the entire vehicle's electrical system.

The manufacturer of the apparatus shall provide the following:

- Documentation of the electrical system performance tests.
- A written load analysis, which shall include the following:
 - The nameplate rating of the alternator.
 - The alternator rating under the conditions specified per:
 - Applicable NFPA 1901 or 1906 (Current Edition).
 - The minimum continuous load of each component that is specified per:
 - Applicable NFPA 1901 or 1906 (Current Edition).
 - Additional loads that, when added to the minimum continuous load, determine the total connected load.
 - Each individual intermittent load.

All of the above listed items shall be provided by the bidder per the applicable NFPA 1901 or 1906 (Current Edition).